

System.UInt16 Structure

```
[ILASM]
.class public sequential sealed serializable UInt16 extends
System.ValueType implements System.IComparable,
System.IFormattable

[C#]
public struct UInt16: IComparable, IFormattable
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 1.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Type Attributes:

- CLSCompliantAttribute(false)

Implements:

- **System.IComparable**
- **System.IFormattable**

Summary

Represents a 16-bit unsigned integer.

Inherits From: System.ValueType

Library: BCL

Thread Safety: This type is safe for multithreaded operations.

Description

The **System.UInt16** data type represents integer values ranging from 0 to positive 65,535 (hexadecimal 0xFFFF).

1 UInt16.MaxValue Field

```
2 [ILASM]  
3 .field public static literal unsigned int16 MaxValue =  
4 65535  
  
5 [C#]  
6 public const ushort MaxValue = 65535
```

7 Summary

8 Contains the maximum value for the **System.UInt16** type.

9 Description

10 The value of this constant is 65,535 (hexadecimal 0xFFFF).

11

1 UInt16.MinValue Field

```
2 [ILASM]  
3 .field public static literal unsigned int16 MinValue = 0  
4 [C#]  
5 public const ushort MinValue = 0
```

6 Summary

7 Contains the minimum value for the **System.UInt16** type.

8 Description

9 The value of this constant is 0.

10

UInt16.CompareTo(System.Object)

Method

```
[ILASM]
.method public final hidebysig virtual int32
CompareTo(object value)

[C#]
public int CompareTo(object value)
```

Summary

Returns the sort order of the current instance compared to the specified **System.Object**.

Parameters

Parameter	Description
<i>value</i>	The System.Object to compare to the current instance.

Return Value

A **System.Int32** containing a value that reflects the sort order of the current instance as compared to *value*. The following table defines the conditions under which the return value is a negative number, zero, or a positive number.

Return Value	Description
Any negative number	Current instance < <i>value</i> .
Zero	Current instance == <i>value</i> .
Any positive number	Current instance > <i>value</i> , or <i>value</i> is a null reference.

Description

[Note: This method is implemented to support the **System.IComparable** interface.]

Exceptions

Exception	Condition
-----------	-----------

1
2
3

System.ArgumentException	<i>value</i> is not a System.UInt16 and is not a null reference.
---------------------------------	---

UInt16.Equals(System.Object) Method

```
[ILASM]
.method public hidebysig virtual bool Equals(object obj)

[C#]
public override bool Equals(object obj)
```

Summary

Determines whether the current instance and the specified **System.Object** represent the same value and type.

Parameters

Parameter	Description
<i>obj</i>	The System.Object to compare to the current instance.

Return Value

true if *obj* represents the same value and type as the current instance. If *obj* is a null reference or is not an instance of **System.UInt16**, returns **false**.

Description

[Note: This method overrides **System.Object.Equals**.]

1 UInt16.GetHashCode() Method

```
2 [ILASM]  
3 .method public hidebysig virtual int32 GetHashCode()  
4  
5 [C#]  
6 public override int GetHashCode()
```

6 Summary

7 Generates a hash code for the current instance.

8 Return Value

9

10 A **System.Int32** containing the hash code for the current instance.

11 Description

12 The algorithm used to generate the hash code is unspecified.

13

14 [*Note:* This method overrides **System.Object.GetHashCode.**]

15

1 UInt16.Parse(System.String) Method

```
2 [ILASM]
3 .method public hidebysig static unsigned int16 Parse(string
4 s)
5
6 [C#]
7 public static ushort Parse(string s)
```

7 Summary

8 Returns the specified **System.String** converted to a **System.UInt16**
9 value.

10 Type Attributes:

- 11 • CLSCompliantAttribute(false)

12 Parameters

Parameter	Description
s	A System.String containing the value to convert. The string is interpreted using the System.Globalization.NumberStyles.Integer style.

16 Return Value

18 The **System.UInt16** value obtained from s.

19 Description

20 This version of **System.UInt16.Parse** is equivalent to
21 **System.UInt16.Parse(s,**
22 **System.Globalization.NumberStyles.Integer, null)**.

23
24 The string s is parsed using the formatting information in a
25 **System.Globalization.NumberFormatInfo** initialized for the current
26 system culture. [Note: For more information, see
27 **System.Globalization.NumberFormatInfo.CurrentInfo**.]

28
29 This method is not CLS-compliant. For a CLS-compliant alternative use
30 **System.Int32.Parse(System.String)**.

31 Exceptions

Exception	Condition
-----------	-----------

System.ArgumentNullException	s is a null reference.
System.FormatException	s is not in the correct style.
System.OverflowException	s represents a number greater than System.UInt16.MaxValue or less than System.UInt16.MinValue .

Example

This example demonstrates parsing a string to a **System.UInt16**.

[C#]

```
using System;
public class UInt16ParseClass {
    public static void Main() {
        string str = " 100 ";
        Console.WriteLine("String: \"{0}\" <UInt16>
{1}",str,UInt16.Parse(str));
    }
}
```

The output is

String: " 100 " <UInt16> 100

UInt16.Parse(System.String, System.Globalization.NumberStyles) Method

```
[ILASM]
.method public hidebysig static unsigned int16 Parse(string
s, valuetype System.Globalization.NumberStyles style)

[C#]
public static ushort Parse(string s, NumberStyles style)
```

Summary

Returns the specified **System.String** converted to a **System.UInt16** value.

Type Attributes:

- CLSCompliantAttribute(false)

Parameters

Parameter	Description
s	A System.String containing the value to convert. The string is interpreted using the style specified by <i>style</i> .
style	Zero or more System.Globalization.NumberStyles values that specify the style of s. Specify multiple values for <i>style</i> using the bitwise OR operator. If <i>style</i> is a null reference, the string is interpreted using the System.Globalization.NumberStyles.Integer style.

Return Value

The **System.UInt16** value obtained from s.

Description

This version of **System.UInt16.Parse** is equivalent to **System.UInt16.Parse(s, style, null)**.

The string s is parsed using the formatting information in a **System.Globalization.NumberFormatInfo** initialized for the current system culture. [Note: For more information, see **System.Globalization.NumberFormatInfo.CurrentInfo**.]

This method is not CLS-compliant. For a CLS-compliant alternative use

1 **System.Int32.Parse(System.String, System.Globalization.Numb**
2 **erStyles).**

3 **Exceptions**

4
5

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.FormatException	s is not in the correct style.
System.OverflowException	s represents a number greater than System.UInt16.MaxValue or less than System.UInt16.MinValue .

6
7
8

1 **UInt16.Parse(System.String,** 2 **System.IFormatProvider) Method**

```
3    [ILASM]  
4    .method public hidebysig static unsigned int16 Parse(string  
5    s, class System.IFormatProvider provider)  
  
6    [C#]  
7    public static ushort Parse(string s, IFormatProvider  
8    provider)
```

9 **Summary**

10 Returns the specified **System.String** converted to a **System.UInt16**
11 value.

12 **Type Attributes:**

- 13 • CLSCompliantAttribute(false)

14 **Parameters**

Parameter	Description
<i>s</i>	A System.String containing the value to convert. The string is interpreted using the System.Globalization.NumberStyles.Integer style.
<i>provider</i>	A System.IFormatProvider that supplies a System.Globalization.NumberFormatInfo containing culture-specific formatting information about <i>s</i> .

18 **Return Value**

20 The **System.UInt16** value obtained from *s*.

21 **Description**

22 This version of **System.UInt16.Parse** is equivalent to
23 **System.UInt16.Parse** (*s*,
24 **System.Globalization.NumberStyles.Integer**, *provider*).

25 The string *s* is parsed using the culture-specific formatting information
26 from the **System.Globalization.NumberFormatInfo** instance
27 supplied by *provider*. If *provider* is **null** or a
28 **System.Globalization.NumberFormatInfo** cannot be obtained from
29 *provider*, the formatting information for the current system culture is
30 used.
31

1
2
3
4
5
6

7
8
9

This method is not CLS-compliant. For a CLS-compliant alternative use **System.Int32.Parse(System.String, System.IFormatProvider)**.

Exceptions

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.FormatException	s is not in the correct style.
System.OverflowException	s represents a number greater than System.UInt16.MaxValue or less than System.UInt16.MinValue .

UInt16.Parse(System.String, System.Globalization.NumberStyles, System.IFormatProvider) Method

```
[ILASM]
.method public hidebysig static unsigned int16 Parse(string
s, valuetype System.Globalization.NumberStyles style, class
System.IFormatProvider provider)
```

```
[C#]
public static ushort Parse(string s, NumberStyles style,
IFormatProvider provider)
```

Summary

Returns the specified **System.String** converted to a **System.UInt16** value.

Type Attributes:

- CLSCompliantAttribute(false)

Parameters

Parameter	Description
<i>s</i>	A System.String containing the value to convert. The string is interpreted using the style specified by <i>style</i> .
<i>style</i>	Zero or more System.Globalization.NumberStyles values that specify the style of <i>s</i> . Specify multiple values for <i>style</i> using the bitwise OR operator. If <i>style</i> is a null reference, the string is interpreted using the System.Globalization.NumberStyles.Integer style.
<i>provider</i>	A System.IFormatProvider that supplies a System.Globalization.NumberFormatInfo containing culture-specific formatting information about <i>s</i> .

Return Value

The **System.UInt16** value obtained from *s*.

Description

The string *s* is parsed using the culture-specific formatting information from the **System.Globalization.NumberFormatInfo** instance supplied by *provider*. If *provider* is **null** or a **System.Globalization.NumberFormatInfo** cannot be obtained from

1 *provider*, the formatting information for the current system culture is
2 used.

3
4 This method is not CLS-compliant. For a CLS-compliant alternative use
5 **System.Int32.Parse(System.String,**
6 **System.Globalization.NumberStyles, System.IFormatProvider).**

7 **Exceptions**

8
9

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.FormatException	s is not in the correct style.
System.OverflowException	s represents a number greater than System.UInt16.MaxValue or less than System.UInt16.MinValue .

10
11
12

1 **UInt16.ToString(System.IFormatProvider** 2 **) Method**

```
3    [ILASM]  
4    .method public final hidebysig virtual string  
5    ToString(class System.IFormatProvider provider)  
  
6    [C#]  
7    public string ToString(IFormatProvider provider)
```

8 **Summary**

9 Returns a **System.String** representation of the value of the current
10 instance.

11 **Parameters**

Parameter	Description
<i>provider</i>	A System.IFormatProvider that supplies a System.Globalization.NumberFormatInfo containing culture-specific formatting information.

14 **Return Value**

17 A **System.String** representation of the current instance formatted
18 using the general format specifier, ("G"). The string takes into account
19 the formatting information in the
20 **System.Globalization.NumberFormatInfo** instance supplied by
21 *provider*.

22 **Description**

23 This version of **System.UInt16.ToString** is equivalent to
24 **System.UInt16.ToString("G", provider)**.

25 If *provider* is null or a **System.Globalization.NumberFormatInfo**
26 cannot be obtained from *provider*, the formatting information for the
27 current system culture is used.
28

UInt16.ToString(System.String, System.IFormatProvider) Method

```
[ILASM]
.method public final hidebysig virtual string
ToString(string format, class System.IFormatProvider
provider)

[C#]
public string ToString(string format, IFormatProvider
provider)
```

Summary

Returns a **System.String** representation of the value of the current instance.

Parameters

Parameter	Description
<i>format</i>	A System.String containing a character that specifies the format of the returned string.
<i>provider</i>	A System.IFormatProvider that supplies a System.Globalization.NumberFormatInfo instance containing culture-specific formatting information.

Return Value

A **System.String** representation of the current instance formatted as specified by *format*. The string takes into account the formatting information in the **System.Globalization.NumberFormatInfo** instance supplied by *provider*.

Description

If *provider* is **null** or a **System.Globalization.NumberFormatInfo** cannot be obtained from *provider*, the formatting information for the current system culture is used.

If *format* is a null reference, the general format specifier "G" is used.

[Note: For a detailed description of formatting, see the **System.IFormattable** interface.]

This method is implemented to support the **System.IFormattable** interface.] The following table lists the characters that are valid for the **System.UInt16** type.

Format Characters	Description
"C", "c"	Currency format.
"D", "d"	Decimal format.
"E", "e"	Exponential notation format.
"F", "f"	Fixed-point format.
"G", "g"	General format.
"N", "n"	Number format.
"P", "p"	Percent format.
"X", "x"	Hexadecimal format.

1

2 Exceptions

3

4

Exception	Condition
System.FormatException	<i>format</i> is invalid.

5

6

7

1 UInt16.ToString() Method

```
2 [ILASM]  
3 .method public hidebysig virtual string ToString()  
  
4 [C#]  
5 public override string ToString()
```

6 Summary

7 Returns a **System.String** representation of the value of the current
8 instance.

9 Return Value

10

11 A **System.String** representation of the current instance formatted
12 using the general format specifier ("G"). The string takes into account
13 the current system culture.

14 Description

15 This version of **System.UInt16.ToString** is equivalent to
16 **System.UInt16.ToString(null, null)**.

17

18 [*Note:* This method overrides **System.Object.ToString**.]

19

UInt16.ToString(System.String) Method

```
[ILASM]
.method public hidebysig instance string ToString(string
format)

[C#]
public string ToString(string format)
```

Summary

Returns a **System.String** representation of the value of the current instance.

Parameters

Parameter	Description
<i>format</i>	A System.String that specifies the format of the returned string. [Note: For a list of valid values, see System.UInt16.ToString(System.String, System.IFormatProvider) .]

Return Value

A **System.String** representation of the current instance formatted as specified by *format*. The string takes into account the current system culture.

Description

This method is equivalent to **System.UInt16.ToString(format, null)**.

If *format* is a null reference, the general format specifier "G" is used.

Exceptions

Exception	Condition
System.FormatException	<i>format</i> is invalid.

Example

This example demonstrates converting a **System.UInt16** to a string.

```
[C#]
```

```

1      using System;
2      public class UInt16ToStringExample {
3          public static void Main() {
4              UInt16 i = 16;
5              Console.WriteLine(i);
6              String[] formats = {"c", "d", "e", "f", "g", "n",
7                  "p", "x" };
8              foreach(String str in formats)
9                  Console.WriteLine("{0}: {1}", str,
10                     i.ToString(str));
11          }
12      }

```

13 The output is

14
15 16

16
17
18 c: \$16.00

19
20
21 d: 16

22
23
24 e: 1.600000e+001

25
26
27 f: 16.00

28
29
30 g: 16

31
32

1	n: 16.00
2	
3	
4	p: 1,600.00 %
5	
6	
7	x: 10
8	
9	