

System.Enum Class

```
[ILASM]
.class public abstract serializable Enum extends
System.ValueType implements System.IComparable,
System.IFormattable

[C#]
public abstract class Enum: ValueType, IComparable,
IFormattable
```

Assembly Info:

- Name: mscorlib
- Public Key: [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- Version: 1.0.x.x
- Attributes:
 - CLSCompliantAttribute(true)

Implements:

- System.IComparable
- System.IFormattable

Summary

Provides support for all enumeration types. Serves as the base class for all enumeration types.

Inherits From: System.ValueType

Library: BCL

Description

A **System.Enum** is a distinct type with named constant members. Each enumeration type has a corresponding integral type called the *underlying type* of the enumeration type. This underlying type is required to be a system supplied integer type that is large enough to represent all values defined in the enumeration. A **System.Enum** declaration is allowed to explicitly declare any integral type other than **System.Char** as an underlying type. This includes **System.Byte**, **System.SByte**, **System.Int16**, **System.Int32**, **System.Int64**, **System.UInt16**, **System.UInt32**, and **System.UInt64**. A **System.Enum** declaration that does not explicitly declare an underlying type has an underlying type of **System.Int32**.

System.Enum derives from **System.ValueType** but is not a value

1 type. Programming languages typically provide syntax to declare sets
2 of a specified enumeration type consisting of named constants and
3 their values.
4
5 It is possible to treat instances of a **System.Enum** as bit fields
6 containing multiple values. For more information, see
7 **System.FlagsAttribute**.
8
9 [Note: **System.Enum** provides methods to compare instances of
10 enumeration types, convert the value of an instance to its
11 **System.String** representation, convert the **System.String**
12 representation of a number to an instance of the enumeration type,
13 and create an instance of a specified enumeration and value.]
14

Enum.CompareTo(System.Object) Method

```
[ILASM]
.method public final hidebysig virtual int32
CompareTo(object target)

[C#]
public int CompareTo(object target)
```

Summary

Returns the sort order of the current instance compared to the specified **System.Object**.

Parameters

Parameter	Description
<i>target</i>	An object to compare the current instance to.

Return Value

A **System.Int32** containing a value that reflects the sort order of the current instance as compared to *target*. The following table defines the conditions under which the returned value is a negative number, zero, or a positive number.

Return Value	Description
Any negative integer	The value of the current instance is less than the value of <i>target</i> .
Zero	The value of the current instance is equal to the value of <i>target</i> .
Any positive integer	The value of the current instance is greater than the value of <i>target</i> , or <i>target</i> is null .

Description

[Note: This method is implemented to support the **System.IComparable** interface.]

Exceptions

Exception	Condition
System.ArgumentException	<i>target</i> and the current instance are not of the same

1
2
3

	enumeration type.
--	-------------------

1 Enum.Equals(System.Object) Method

```
2 [ILASM]
3 .method public hidebysig virtual bool Equals(object obj)
4
5 [C#]
6 public override bool Equals(object obj)
```

6 Summary

7 Determines whether the current instance and the specified
8 **System.Object** represent the same type and value.

9 Parameters

10
11

Parameter	Description
<i>obj</i>	An object to compare the current instance to.

12
13
14

Return Value

15 **true** if *obj* is of the same enumeration type and represents the same
16 value as the current instance; otherwise, **false**.

17 Description

18 [Note: This method overrides **System.Object.Equals**.]
19

Enum.Format(System.Type, System.Object, System.String) Method

```
[ILASM]
.method public hidebysig static string Format(class
System.Type enumType, object value, string format)

[C#]
public static string Format(Type enumType, object value,
string format)
```

Summary

Converts the specified element of the specified enumeration type to its **System.String** representation using the specified format.

Parameters

Parameter	Description
<i>enumType</i>	A System.Type that specifies the type of the enumeration of which <i>value</i> is a member.
<i>value</i>	The enumeration element to be converted.
<i>format</i>	A System.String that specifies the output format to use.

Return Value

The **System.String** representation of the value of the enumeration element.

Description

For cross-platform portability, the only valid values for *format* are:

Format	Description
"G" or "g"	If <i>value</i> is equal to a defined value of <i>enumType</i> , returns the element name defined for <i>value</i> . If the System.FlagsAttribute attribute is set on the System.Enum declaration and <i>value</i> is a built-in integer type and is equal to a summation of enumeration elements, the return value contains the element names in an unspecified order, separated by commas (e.g. "Red, Yellow"). Otherwise, <i>value</i> is returned in decimal format.
"X" or "x"	Returns <i>value</i> in hexadecimal format, without a leading 0x. The value is padded with leading zeroes to ensure the returned value is at least eight digits in length.
"F" or "f"	Behaves identically to "G". except the FlagsAttribute is not required to be

"f"	present on the System.Enum declaration.
"D" or "d"	Returns <i>value</i> in decimal format with no leading zeroes.

1

2 Exceptions

3

4

Exception	Condition
System.ArgumentNullException	<i>enumType</i> , <i>value</i> or <i>format</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Enum . -or- <i>value</i> is neither of type <i>enumType</i> nor does it have the same underlying type as <i>enumType</i> .
System.FormatException	<i>format</i> contains an invalid value.

5

6 Example

7

8 The following example demonstrates formatting enumeration values.

9

10

[C#]

11

```
using System;
```

12

```
public enum Signs {
```

13

```
    Stop = 1,
```

14

```
    Yield = 2,
```

15

```
    Merge = 4
```

16

```
};
```

17

```
[Flags]
```

18

```
public enum Lights {
```

19

```
    Red = 1,
```

20

```
    Yellow = 2,
```

21

```
    Green = 4
```

22

```
};
```

23

```
public class EnumCompTo {
```

24

```
    public static void Main() {
```

25

```
        Console.WriteLine(Signs.Format(typeof(Signs),
```

26

```
Signs.Merge, "d"));
```

27

```
        Console.WriteLine(Signs.Format(typeof(Signs), 7, "g"));
```

28

```
        Console.WriteLine(Lights.Format(typeof(Lights),
```

29

```
Lights.Yellow, "x"));
```

30

```
        Console.WriteLine(Lights.Format(typeof(Lights), 7,
```

31

```
"g"));
```

32

```
    }
```

33

```
}
```

34

```
1      The output is
2
3      4
4
5
6      7
7
8
9      00000002
10
11
12     Red, Yellow, Green
13
```

14

1 Enum.GetHashCode() Method

```
2 [ILASM]  
3 .method public hidebysig virtual int32 GetHashCode()  
  
4 [C#]  
5 public override int GetHashCode()
```

6 Summary

7 Generates a hash code for the current instance.

8 Return Value

9

10 A **System.Int32** containing a hash code for the current instance.

11 Description

12 The algorithm used to generate the hash code is unspecified.

13

14 [*Note:* This method overrides **System.Object.GetHashCode.**]

15

Enum.GetName(System.Type, System.Object) Method

```
[ILASM]
.method public hidebysig static string GetName(class
System.Type enumType, object value)

[C#]
public static string GetName(Type enumType, object value)
```

Summary

Retrieves the name of the constant of the specified enumeration type that has the specified value.

Parameters

Parameter	Description
<i>enumType</i>	A System.Type that specifies the type of the enumeration.
<i>value</i>	A System.Object that contains the integral value or the name of an enumeration constant.

Return Value

A **System.String** containing the name of the enumerated constant in *enumType* whose value is *value*, or a null reference if no such constant is found.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> or <i>value</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum . -or- <i>value</i> is neither of type <i>enumType</i> nor does it have the same underlying type as <i>enumType</i> .

Example

```
1      The following example demonstrates the System.Enum.GetName
2      method.
3
4      [C#]
5
6      using System;
7      public enum Signs {
8          Stop = 1,
9          Yield = 2,
10         Merge = 4
11     };
12     public class EnumCompTo {
13         public static void Main() {
14             Console.Write("The name of the constant with the value 4
15             is: ");
16             Console.WriteLine("{0}.", Signs.GetName(typeof(Signs),
17             4));
18             Console.Write("The name of the constant with the value
19             Stop is: ");
20             Console.WriteLine("{0}.", Signs.GetName(typeof(Signs),
21             Signs.Stop));
22         }
23     }
24
25     The output is
26
27     The name of the constant with the value 4 is: Merge.
28
29     The name of the constant with the value Stop is: Stop.
```

30

Enum.GetNames(System.Type) Method

```
[ILASM]
.method public hidebysig static class System.String[]
GetNames(class System.Type enumType)

[C#]
public static string[] GetNames(Type enumType)
```

Summary

Returns a zero-based, one-dimensional **System.String** array that contains the names of the constants of the specified enumeration type.

Parameters

Parameter	Description
<i>enumType</i>	A System.Type that specifies the type of an enumeration.

Return Value

A **System.String** vector of the names of the constants in *enumType*. The elements of the vector are sorted by the values of the enumerated constants.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Example

The following example demonstrates the **System.Enum.GetNames** method.

```
[C#]

using System;

public enum Colors {
    Red,
    White,
```

```

1      Blue
2  };
3
4  public class enumGetNames {
5
6      public static void Main() {
7          int i = 0;
8          String[] strAry = Colors.GetNames(typeof(Colors));
9          foreach (String str in strAry) {
10             Console.Write("The value indexed '{0}' ", i++);
11             Console.WriteLine("is {0}.", str);
12         }
13     }
14 }

```

```

15 The output is
16
17 The value indexed '0' is Red.
18
19
20 The value indexed '1' is White.
21
22
23 The value indexed '2' is Blue.
24

```

25

Enum.GetUnderlyingType(System.Type)

Method

```
[ILASM]
.method public hidebysig static class System.Type
GetUnderlyingType(class System.Type enumType)

[C#]
public static Type GetUnderlyingType(Type enumType)
```

Summary

Returns the underlying type of the specified enumeration type.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.

Return Value

A **System.Type** instance that describes the underlying type of *enumType*.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not an enumeration type.

Example

The following example demonstrates the **System.Enum.GetUnderlyingType** method.

```
[C#]

using System;
public enum Colors {
    Red,
    White,
    Blue
}
```

```
1 public class EnumUnderlyingTypeTest {  
2     public static void Main() {  
3         Type t = Colors.GetUnderlyingType(typeof(Colors));  
4         Console.WriteLine("The underlying type of Colors is  
5 {0}.", t.ToString());  
6     }  
7 }
```

8 The output is

9
10 The underlying type of Colors is System.Int32.
11

12

Enum.GetValues(System.Type) Method

```
[ILASM]
.method public hidebysig static class System.Array
GetValues(class System.Type enumType)

[C#]
public static Array GetValues(Type enumType)
```

Summary

Returns a zero-based, one-dimensional array of the values of the constants of the specified enumeration type.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.

Return Value

A vector of the enumeration type specified by *enumType* containing the values of the constants in *enumType*. The elements of the array are sorted by the values of the enumeration constants.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not an enumeration type.

Example

The following example demonstrates the **System.Enum.GetValues** method.

```
[C#]

using System;
public enum Colors {
    Red = 1,
    White = 2,
    Blue = 4
}
```



```
1 public class enumGetValues {
2     public static void Main() {
3         Array valueAry = Enum.GetValues(typeof(Colors));
4         foreach (int i in valueAry) {
5             Console.WriteLine("The value of element {0} is
6 {1}",
7     Enum.Format(typeof(Colors), i, "g"),i);
8         }
9     }
10 }
```

11 The output is

12
13 The value of element Red is 1.

14
15
16 The value of element White is 2.

17
18
19 The value of element Blue is 4.

20

21

Enum.IsDefined(System.Type, System.Object) Method

```
[ILASM]
.method public hidebysig static bool IsDefined(class
System.Type enumType, object value)

[C#]
public static bool IsDefined(Type enumType, object value)
```

Summary

Returns a **System.Boolean** indicating whether a constant with the specified value exists in the specified enumeration type.

Parameters

Parameter	Description
<i>enumType</i>	A System.Type that describes an enumeration.
<i>value</i>	The constant or value being searched for in <i>enumType</i> .

Return Value

true if a constant in the enumeration described by *enumType* has a value equal to *value*; otherwise, **false**.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> or <i>value</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not an enumeration type.
	-or- The type of <i>value</i> is not an <i>enumType</i> or an underlying type of <i>enumType</i> .

Example

The following example demonstrates the **System.Enum.IsDefined** method.

```

1
2    [C#]

3    using System;
4    public enum Colors {
5        Red = 1,
6        White = 2,
7        Blue = 4
8    }
9    public class enumIsDefined {
10        public static void Main() {
11            Console.Write("It is {0} ",
12            Enum.IsDefined(typeof(Colors), 1));
13            Console.WriteLine("that '1' is defined in 'Colors'.");
14            Console.Write("It is {0} ",
15            Enum.IsDefined(typeof(Colors), 3));
16            Console.WriteLine("that '3' is defined in 'Colors'.");
17        }
18    }

```

```

19    The output is
20
21    It is True that '1' is defined in 'Colors'.
22
23
24    It is False that '3' is defined in 'Colors'.
25

```

26

Enum.Parse(System.Type, System.String)

Method

```
[ILASM]  
.method public hidebysig static object Parse(class  
System.Type enumType, string value)  
  
[C#]  
public static object Parse(Type enumType, string value)
```

Summary

Converts the specified **System.String** representation of one or more enumerated constants of a specified enumeration type to an equivalent enumerated object.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	A System.String containing one or more names or a single numeric value to convert. If the string contains more than one name, each name is required to be separated by a comma (','),. The names are parsed in a case-sensitive manner. The names or number can be surrounded by any amount of white space.

Return Value

A **System.Object** of type *enumType* whose values are represented by *value*.

Description

This version of **System.Enum.Parse** is equivalent to **System.Enum.Parse** (*enumType*, *value*, **false**).

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> or <i>value</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum . -or-

	<p><i>value</i> is either equal to System.String.Empty or contains only white space.</p> <p>-or-</p> <p><i>value</i> represents one or more names, and at least one name represented by <i>value</i> is not of type <i>enumType</i>.</p>
--	---

Example

The following example demonstrates the **System.Enum.Parse** method.

[C#]

```
using System;
public enum Colors {
    Red = 1,
    Blue = 2
}
public class enumTest {
    public static void Main() {
        object o = Enum.Parse(typeof (Colors), "Red, Blue");
        Type oType = o.GetType();
        Console.WriteLine("The type of the object returned is
{0}",oType.ToString());
        Array values = Enum.GetValues(oType);
        foreach (Colors c in values) {
            Console.WriteLine(Enum.Format(oType,c,"D"));
        }
    }
}
```

The output is

The type of the object returned is Colors

1

1	2
2	
3	

Enum.Parse(System.Type, System.String, System.Boolean) Method

```
[ILASM]
.method public hidebysig static object Parse(class
System.Type enumType, string value, bool ignoreCase)

[C#]
public static object Parse(Type enumType, string value,
bool ignoreCase)
```

Summary

Converts the specified **System.String** representation of one or more enumerated constants of a specified enumeration type to an equivalent enumerated object. This method behaves in a case-sensitive or insensitive manner according to the specified **System.Boolean**.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	A System.String containing one or more names or a single numeric value to convert. If the string contains more than one name, each name is required to be separated by a comma (','),. The names or number can be surrounded by any amount of white space.
<i>ignoreCase</i>	A System.Boolean value. Specify true to have names in <i>value</i> parsed in a case-insensitive manner. Specify false to have names parsed in a case-sensitive manner.

Return Value

A **System.Object** of type *enumType* whose values are represented by *value*.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> or <i>value</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

	<p>-or-</p> <p><i>value</i> is either equal to System.String.Empty or contains only white space.</p> <p>-or-</p> <p><i>value</i> represents one or more names, and at least one name represented by <i>value</i> is not of type <i>enumType</i>.</p>
--	---

1

2 **Example**

3

4 For an example that demonstrates parsing strings containing
5 enumeration values, see **System.Enum.Parse(System.Type,**
6 **System.String)**.

7

Enum.ToObject(System.Type, System.Object) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, object value)

[C#]
public static object ToObject(Type enumType, object value)
```

Summary

Returns an instance of the specified enumeration type set to the specified value.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of the enumeration.
<i>value</i>	The value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.SByte) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, int8 value)

[C#]
public static object ToObject(Type enumType, sbyte value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.SByte** value.

Type Attributes:

- CLSCompliantAttribute(false)

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.SByte value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Description

This member is not CLS-compliant. For a CLS-compliant alternative, use **System.Enum.ToObject(System.Type, System.Int16)**.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.Int16) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, int16 value)

[C#]
public static object ToObject(Type enumType, short value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.Int16** value.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.Int16 value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.Int32) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, int32 value)

[C#]
public static object ToObject(Type enumType, int value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.Int32** value.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.Int32 value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.Byte) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, unsigned int8 value)

[C#]
public static object ToObject(Type enumType, byte value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.Byte** value.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.Byte value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.UInt16) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, unsigned int16 value)

[C#]
public static object ToObject(Type enumType, ushort value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.UInt16** value.

Type Attributes:

- CLSCompliantAttribute(false)

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.UInt16 value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Description

This member is not CLS-compliant. For a CLS-compliant alternative, use **System.Enum.ToObject(System.Type, System.Int32)**.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.UInt32) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, unsigned int32 value)

[C#]
public static object ToObject(Type enumType, uint value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.UInt32** value.

Type Attributes:

- CLSCompliantAttribute(false)

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.UInt32 value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Description

This member is not CLS-compliant. For a CLS-compliant alternative, use **System.Enum.ToObject(System.Type, System.Int64)**.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.Int64) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, int64 value)

[C#]
public static object ToObject(Type enumType, long value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.Int64** value.

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.Int64 value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToObject(System.Type, System.UInt64) Method

```
[ILASM]
.method public hidebysig static object ToObject(class
System.Type enumType, unsigned int64 value)

[C#]
public static object ToObject(Type enumType, ulong value)
```

Summary

Returns an instance of the specified enumeration type set to the specified **System.UInt64** value.

Type Attributes:

- CLSCompliantAttribute(false)

Parameters

Parameter	Description
<i>enumType</i>	The System.Type of an enumeration.
<i>value</i>	The System.UInt64 value to set.

Return Value

An enumeration object of type *enumType* whose value is *value*.

Description

This member is not CLS-compliant. For a CLS-compliant alternative, use **System.Enum.ToObject(System.Type, System.Int64)**.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>enumType</i> is a null reference.
System.ArgumentException	<i>enumType</i> is not a System.Type that describes a System.Enum .

Enum.ToString(System.IFormatProvider)

Method

```
[ILASM]
.method public final hidebysig virtual string
ToString(class System.IFormatProvider provider)

[C#]
public string ToString(IFormatProvider provider)
```

Summary

Converts the name of the value of the current instance to its equivalent **System.String** representation.

Parameters

Parameter	Description
<i>provider</i>	An object that implements the System.IFormatProvider interface or a null reference. The System.IFormatProvider is not used in the implementation of this method. [Note: There is no System.IFormatProvider that corresponds to a System.Enum object; therefore, <i>provider</i> is not utilized by this method, and any System.IFormatProvider may be passed as a parameter.]

Return Value

The **System.String** representation of the name of the value of the current instance.

Description

This method is equivalent to the version of **System.Enum.ToString** that takes no arguments.

Enum.ToString(System.String, System.IFormatProvider) Method

```
[ILASM]
.method public final hidebysig virtual string
ToString(string format, class System.IFormatProvider
provider)

[C#]
public string ToString(string format, IFormatProvider
provider)
```

Summary

Converts the numeric value of the current instance to its equivalent **System.String** representation using the specified format.

Parameters

Parameter	Description
<i>format</i>	A System.String that specifies the format to use when converting the current instance to a System.String . Specify one of the following values in upper or lower case: "G", "D", "X", or "F".
<i>provider</i>	An object that implements the System.IFormatProvider interface or a null reference. The System.IFormatProvider is not used in the implementation of this method. [Note: There is no System.IFormatProvider that corresponds to a System.Enum object; therefore, <i>provider</i> is not utilized by this method, and any System.IFormatProvider may be passed as a parameter.]

Return Value

The **System.String** representation of the value of the current instance as specified by *format*.

Description

If *format* is a null reference or an empty string, the return value is formatted using the general format specifier ("G").

[Note: For details on the format specifiers used with an enumeration object, see **System.Enum.Format**.

This method is implemented to support the **System.IFormattable** interface.]

1 **Exceptions**

2

3

Exception	Condition
System.FormatException	<i>format</i> does not contain a valid format specifier.

4

5

6

1 Enum.ToString() Method

```
2 [ILASM]  
3 .method public hidebysig virtual string ToString()  
  
4 [C#]  
5 public override string ToString()
```

6 Summary

7 Converts the name of the value of the current instance to its
8 equivalent **System.String** representation.

9 Return Value

10

11 The **System.String** representation of the named constant specified by
12 the current instance.

13 Description

14 This version of **System.Enum.ToString** is equivalent to
15 **System.Enum.ToString** ("G", null).
16

17 This method returns the same value as **System.Enum.Format** with
18 the "g" or "G" format option.
19

20 An instance of an enumeration is set to a named constant value. This
21 method returns the name of the constant an instance is set to, not the
22 value itself.

23

Enum.ToString(System.String) Method

```
[ILASM]
.method public hidebysig instance string ToString(string
format)

[C#]
public string ToString(string format)
```

Summary

Converts the value of the current instance to its equivalent **System.String** representation using the specified format.

Parameters

Parameter	Description
<i>format</i>	A System.String that specifies the format to use when converting the current instance to a System.String . Specify one of the following values in upper or lower case: "G", "D", "X", or "F".

Return Value

The **System.String** representation of the value of the current instance as specified by *format*.

Description

If *format* is a null reference or an empty string, the return value is formatted using the general format specifier ("G").

[Note: For details on the format specifiers used with an enumeration object, see **System.Enum.Format**.]

Exceptions

Exception	Condition
System.FormatException	<i>format</i> contains an invalid value.