

# System.Runtime.CompilerServices.MethodImplOptions Enum

```
[ILASM]
.class public sealed serializable MethodImplOptions extends
System.Enum

[C#]
public enum MethodImplOptions
```

## Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 1.0.x.x
- *Attributes:*
  - CLSCompliantAttribute(true)

## Summary

Defines the details of how a method is implemented.

## Inherits From: System.Enum

**Library:** RuntimeInfrastructure

## Description

This enumeration is used by  
**System.Runtime.CompilerServices.MethodImplOptionsAttribute.**

# 1    **MethodImplOptions.ForwardRef Field**

```
2        [ILASM]  
3        .field public static literal valuetype  
4        System.Runtime.CompilerServices.MethodImplOptions  
5        ForwardRef = 16  
  
6        [C#]  
7        ForwardRef = 16
```

## 8    **Summary**

9        Specifies that the method is declared, but its implementation is  
10       provided elsewhere.  
11  
12       [*Note:* For most languages, it is recommended that the notion of  
13       "forward" be attached to methods using language syntax instead of  
14       custom attributes.]

15

# 1 MethodImplOptions.InternalCall Field

```
2 [ILASM]
3 .field public static literal valuetype
4 System.Runtime.CompilerServices.MethodImplOptions
5 InternalCall = 4096

6 [C#]
7 InternalCall = 4096
```

## 8 Summary

9 Specifies an internal call.

10  
11 [Note: An internal call is a call to a method implemented within the  
12 system itself, providing additional functionality that regular managed  
13 code cannot provide. **System.Object.MemberwiseClone** is an  
14 example of an internally called method.]

15

# 1    **MethodImplOptions.NoInlining Field**

```
2        [ILASM]  
3        .field public static literal valuetype  
4        System.Runtime.CompilerServices.MethodImplOptions  
5        NoInlining = 8  
  
6        [C#]  
7        NoInlining = 8
```

## 8    **Summary**

9        Specifies that the method is not permitted to be inlined.

10

# MethodImplOptions.Synchronized Field

```
[ILASM]
.field public static literal valuetype
System.Runtime.CompilerServices.MethodImplOptions
Synchronized = 32

[C#]
Synchronized = 32
```

## Summary

Specifies the method can be executed by only one thread at a time.

This option specifies that before a thread can execute the target method, the thread is required to acquire a lock on either the current instance or the **System.Type** object for the method's class. If the target method is an instance method, the lock is on the current instance. If the target is a static method, the lock is on the **System.Type** object. Specifying this option causes the target method to behave as though its statements are enclosed by **System.Threading.Monitor.Enter** and **System.Threading.Monitor.Exit** statements locking the previous described object. This option and the **System.Threading.Monitor** methods are functionally equivalent, and both are functionally equivalent to enclosing the target method's code in a C# lock (this) statement.

[Note: Because this option holds the lock for the duration of the target method, it should be used only when the entire method must be single threaded. Use the **System.Threading.Monitor** methods (or the C# lock statement) if the object lock can be taken after the method begins, or released before the method ends. Any mechanism that uses locks can cause an application to experience deadlocks and performance degradation; for these reasons, use this option with care.

For most languages, it is recommended that the notion of "synchronized" be attached to methods using language syntax instead of custom attributes.]

# 1 MethodImplOptions.Unmanaged Field

```
2 [ILASM]  
3 .field public static literal valuetype  
4 System.Runtime.CompilerServices.MethodImplOptions Unmanaged  
5 = 4  
  
6 [C#]  
7 Unmanaged = 4
```

## 8 Summary

9 Specifies that the method is implemented in unmanaged code.

10