

System.IO.FileMode Enum

```
[ILASM]
.class public sealed serializable FileMode extends
System.Enum

[C#]
public enum FileMode
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 1.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Summary

Specifies how the operating system opens a file.

Inherits From: System.Enum

Library: BCL

Description

System.IO.FileMode values specify whether a file is created if one does not exist, and determine whether the contents of existing files are retained or overwritten.

1 FileMode.Append Field

```
2 [ILASM]  
3 .field public static literal valuetype System.IO.FileMode  
4 Append = 6  
  
5 [C#]  
6 Append = 6
```

7 Summary

8 Requests a file be opened. If the file exists, its contents are preserved.
9 This value is valid only for **System.IO.FileAccess.Write** access.
10 Attempts to read from a file opened with **Append** cause an exception.
11

1 FileMode.Create Field

```
2        [ILASM]  
3        .field public static literal valuetype System.IO.FileMode  
4        Create = 2  
  
5        [C#]  
6        Create = 2
```

7 Summary

8 Requests a new file be created if it does not exist. The file contents are
9 overwritten if it does exist. This value is equivalent to requesting that
10 if the file does not exist, use **System.IO.FileMode.CreateNew**;
11 otherwise, use **System.IO.FileMode.Truncate**.

12

1 FileMode.CreateNew Field

```
2   [ILASM]  
3   .field public static literal valuetype System.IO.FileMode  
4   CreateNew = 1  
  
5   [C#]  
6   CreateNew = 1
```

7 Summary

8 Requests a new file be created. An exception is thrown if the file
9 already exists.

10

1 FileMode.Open Field

```
2 [ILASM]  
3 .field public static literal valuetype System.IO.FileMode  
4 Open = 3  
  
5 [C#]  
6 Open = 3
```

7 Summary

8 Requests an existing file be opened. An exception is thrown if the file
9 does not exist.

10

1 FileMode.OpenOrCreate Field

```
2 [ILASM]  
3 .field public static literal valuetype System.IO.FileMode  
4 OpenOrCreate = 4  
  
5 [C#]  
6 OpenOrCreate = 4
```

7 Summary

8 Requests a file be opened. The file is created if it does not exist.

9

1 FileMode.Truncate Field

```
2 [ILASM]  
3 .field public static literal valuetype System.IO.FileMode  
4 Truncate = 5  
  
5 [C#]  
6 Truncate = 5
```

7 Summary

8 Requests an existing file be opened; existing contents are deleted.
9 This value is valid only for **System.IO.FileAccess.Write** access.
10 Attempts to read from a file opened with **Truncate** cause an
11 exception.
12