

# System.Threading.Thread Class

```
[ILASM]
.class public sealed Thread extends System.Object

[C#]
public sealed class Thread
```

## Assembly Info:

- Name: mscorlib
- Public Key: [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- Version: 1.0.x.x
- Attributes:
  - CLSCompliantAttribute(true)

## Summary

Represents a sequential thread of execution.

## Inherits From: System.Object

## Library: BCL

**Thread Safety:** All public static members of this type are safe for multithreaded operations. No instance members are guaranteed to be thread safe.

## Description

A process may create and execute one or more threads to execute a portion of the program code associated with the process. A **System.Threading.ThreadStart** delegate is used to specify the program code executed by a thread.

Some operating systems might not utilize the concepts of threads or preemptive scheduling. Also, the concept of "thread priority" might not exist at all or its meaning may vary, depending on the underlying operating system. Implementers of the **System.Threading.Thread** type are required to describe their threading policies, including what thread priority means, how many threading priority levels exist, and whether scheduling is preemptive.

For the duration of its existence, a thread is always in one or more of the states defined by **System.Threading.ThreadState**. A scheduling priority level, as defined by **System.Threading.ThreadPriority**, can be requested for a thread, but it might not be honored by the operating system.

1 If an unhandled exception is thrown in the code executed by a thread  
2 created by an application, a  
3 **System.AppDomain.UnhandledException** event is raised  
4 (**System.UnhandledExceptionEventArgs.IsTerminating** is set to  
5 **false**), and the thread is terminated; the current process is not  
6 terminated.

7

# Thread(System.Threading.ThreadStart)

## Constructor

```
[ILASM]
public rtspecialname specialname instance void .ctor(class
System.Threading.ThreadStart start)

[C#]
public Thread(ThreadStart start)
```

### Summary

Constructs and initializes a new instance of the **System.Threading.Thread** class.

### Parameters

Parameter	Description
<i>start</i>	A <b>System.Threading.ThreadStart</b> delegate that references the methods to be invoked when the new thread begins executing.

[Note: To schedule the thread for execution, call **System.Threading.Thread.Start**.]

Until **System.Threading.Thread.Start** is called, the thread's state includes **System.Threading.ThreadState.Unstarted**.

### Exceptions

Exception	Condition
<b>System.ArgumentNullException</b>	<i>start</i> is <b>null</b> .

# Thread.Abort(System.Object) Method

```
[ILASM]
.method public hidebysig instance void Abort(object
stateInfo)

[C#]
public void Abort(object stateInfo)
```

## Summary

Raises a **System.Threading.ThreadAbortException** in the thread on which it is invoked to begin the process of terminating the thread. In all but the most extraordinary situations, calling this method will terminate the thread.

## Parameters

Parameter	Description
<i>stateInfo</i>	A <b>System.Object</b> that contains application-specific information, such as state, which can be used by the thread being aborted.

## Description

The object passed as the *stateInfo* parameter can be obtained by accessing the **System.Threading.ThreadAbortException.ExceptionState** property.

[Note: For details on aborting threads, see **System.Threading.Thread.Abort ()**.]

## Exceptions

Exception	Condition
<b>System.Security.SecurityException</b>	Caller does not have <b>System.Security.Permissions.SecurityPermission ControlThread</b> security permission for this thread.

## Permissions

Permission	Description
<b>System.Security.SecurityPermission</b>	Requires permission to control the thread to be aborted. See

1  
2  
3

	<b>System.Security.Permissions.SecurityPermissi ControlThread.</b>
--	--

# 1 Thread.Abort() Method

```
2 [ILASM]  
3 .method public hidebysig instance void Abort()  
  
4 [C#]  
5 public void Abort()
```

## 6 Summary

7 Raises a **System.Threading.ThreadAbortException** in the thread  
8 on which it is invoked to begin the process of terminating the thread.  
9 In all but the most extraordinary situations, calling this method will  
10 terminate the thread.

## 11 Description

12 When this method is invoked on a thread, the system throws a  
13 **System.Threading.ThreadAbortException** in the thread to abort it.  
14 Invoking **System.Threading.Thread.Abort** on a thread is similar to  
15 arranging for the target thread to throw a  
16 **System.Threading.ThreadAbortException**. Because, unlike other  
17 exceptions, a **System.Threading.ThreadAbortException** is sent to  
18 another thread, the exception might be delayed. A  
19 **System.Threading.ThreadAbortException** is required to be delayed  
20 if and while the target thread is executing any of the following:

- 21 • unmanaged code
- 22 • a catch handler
- 23 • a finally clause
- 24 • a filter clause
- 25 • a type initializer

26 A thread abort proceeds as follows:

- 27 1. An abort begins at the earliest of the following times:
  - 28 a. when the thread transitions from unmanaged to managed  
29 code execution;
  - 30 b. when the thread finishes the outermost currently executing  
31 catch handler;
  - 32 c. immediately if the thread is running managed code outside of  
33 any catch handler, finally clause, filter clause or type initializer  
34  
35  
36

- 1           2. Whenever an outermost catch handler finishes execution, the  
2           **System.Threading.ThreadAbortException** is rethrown  
3           unless the thread being aborted has called  
4           **System.Threading.Thread.ResetAbort** since the call to  
5           **System.Threading.Thread.Abort**.
- 6           3. When all finally blocks have been called and the thread is about  
7           to transition to any unmanaged code which executed before the  
8           first entry to managed code,  
9           **System.Threading.Thread.ResetAbort** is called so that a  
10          return to managed code will consider the abort to have been  
11          successfully processed.

12          Unexecuted **finally** blocks are executed before the thread is aborted;  
13          this includes any finally block that is executing when the exception is  
14          thrown. The thread is not guaranteed to abort immediately, or at all.  
15          This situation can occur if a thread does an unbounded amount of  
16          computation in the finally blocks that are called as part of the abort  
17          procedure, thereby indefinitely delaying the abort. To ensure a thread  
18          has aborted, invoke **System.Threading.Thread.Join** on the thread  
19          after calling **System.Threading.Thread.Abort**.

20  
21          If **System.Threading.Thread.Abort** is called on a thread that has  
22          not been started, the thread aborts when  
23          **System.Threading.Thread.Start** is called. If the target thread is  
24          blocked or sleeping in managed code and is not inside any of the code  
25          blocks that are required to delay an abort, the thread is resumed and  
26          immediately aborted.

27  
28          After **System.Threading.Thread.Abort** is invoked on a thread, the  
29          state of the thread includes  
30          **System.Threading.ThreadState.AbortRequested**. After the thread  
31          has terminated as a result of a successful call to  
32          **System.Threading.Thread.Abort**, the state of the thread includes  
33          **System.Threading.ThreadState.Stopped** and  
34          **System.Threading.ThreadState.Aborted**.

35  
36          [Note: With sufficient permissions, a thread that is the target of a  
37          **System.Threading.Thread.Abort** can cancel the abort using the  
38          **System.Threading.Thread.ResetAbort** method. For an example  
39          that demonstrates calling the  
40          **System.Threading.Thread.ResetAbort** method, see  
41          **System.Threading.ThreadAbortException**.]

## 42          Exceptions

43  
44

1  
2  
3  
4  
  
5  
6  
7

Permissions

Exception	Condition
<b>System.Security.SecurityException</b>	Caller does not have <b>System.Security.Permissions.SecurityPermission ControlThread</b> security permission for the thread t aborted.

Permission	Description
<b>System.Security.SecurityPermission</b>	Requires permission to control the thread to be ab See <b>System.Security.Permissions.SecurityPermissi ControlThread</b> .



# 1 Thread.Finalize() Method

```
2 [ILASM]  
3 .method family hidebysig virtual void Finalize()  
4  
5 [C#]  
6 ~Thread()
```

## 6 Summary

7 Releases the resources held by this instance.

## 8 Description

9 [Note: Application code does not call this method; it is automatically  
10 invoked during garbage collection.]

11

The following member must be implemented if the RuntimeInfrastructure library is present in the implementation.

## Thread.GetDomain() Method

```
[ILASM]
.method public hidebysig static class System.AppDomain
GetDomain()

[C#]
public static AppDomain GetDomain()
```

### Summary

Returns an object representing the application domain in which the current thread is executing.

### Return Value

A **System.AppDomain** object that represents the current application domain.

# 1 Thread.Join() Method

```
2 [ILASM]
3 .method public hidebysig instance void Join()
4
5 [C#]
6 public void Join()
```

## 6 Summary

7 Blocks the calling thread until the thread on which this method is  
8 invoked terminates.

## 9 Description

10 [Note: Use this method to ensure a thread has terminated. The caller  
11 will block indefinitely if the thread does not terminate.]

12  
13 **System.Threading.Thread.Join** cannot be invoked on a thread that  
14 is in the **System.Threading.ThreadState.Unstarted** state.

15  
16 This method changes the state of the calling thread to include  
17 **System.Threading.ThreadState.WaitSleepJoin**.

## 18 Exceptions

Exception	Condition
<b>System.Threading.ThreadStateException</b>	The caller attempted to join a thread that is in the <b>System.Threading.ThreadState.Unstarted</b> state.

# Thread.Join(System.Int32) Method

```
[ILASM]
.method public hidebysig instance bool Join(int32
millisecondsTimeout)

[C#]
public bool Join(int millisecondsTimeout)
```

## Summary

Blocks the calling thread until the thread on which this method is invoked terminates or the specified time elapses.

## Parameters

Parameter	Description
<i>millisecondsTimeout</i>	A <b>System.Int32</b> containing the number of milliseconds to wait for the thread to terminate.

## Return Value

**true** if the thread has terminated; **false** if the thread has not terminated after *millisecondsTimeout* has elapsed.

## Description

[Note: If **System.Threading.Timeout.Infinite** is specified for *millisecondsTimeout*, this method behaves identically to **Join ()**, except for the return value.]

**Join** cannot be invoked on a thread that is in the **System.Threading.ThreadState.Unstarted** state.

This method changes the state of the calling thread to include **System.Threading.ThreadState.WaitSleepJoin**.

## Exceptions

Exception	Condition
<b>System.ArgumentOutOfRangeException</b>	The value of <i>millisecondsTimeout</i> is negative and is not equal to <b>System.Threading.Timeout.Infinite</b> .
<b>System.Threading.ThreadStateException</b>	The caller attempted to join a thread that is in the

1  
2  
3

	<b>System.Threading.ThreadState.Unstarted</b> state.
--	---

# Thread.Join(System.TimeSpan) Method

```
[ILASM]
.method public hidebysig instance bool Join(valuetype
System.TimeSpan timeout)

[C#]
public bool Join(TimeSpan timeout)
```

## Summary

Blocks the calling thread until the thread on which this method is invoked terminates or the specified time elapses.

## Parameters

Parameter	Description
<i>timeout</i>	A <b>System.TimeSpan</b> set to the amount of time to wait for the thread to terminate. Specify <b>System.Threading.Timeout.Infinite</b> milliseconds to wait indefinitely.

## Return Value

**true** if the thread has terminated; **false** if the thread has not terminated after the amount of time specified by *timeout* has elapsed.

## Description

This method converts *timeout* to milliseconds, tests the validity of the converted value, and calls **System.Threading.Thread.Join(System.Int32)**.

[Note: If **System.Threading.Timeout.Infinite** milliseconds is specified for *timeout*, this method behaves identically to **Join ()**, except for the return value.]

**Join** cannot be invoked on a thread that is in the **System.Threading.ThreadState.Unstarted** state.

This method changes the state of the current thread to include **System.Threading.ThreadState.WaitSleepJoin**.

## Exceptions

Exception	Condition
-----------	-----------

1  
2  
3

<b>System.ArgumentOutOfRangeException</b>	The value of <i>timeout</i> is negative and is not equal to <b>System.Threading.Timeout.Infinite</b> milliseconds, or is greater than <b>System.Int32.MaxValue</b> milliseconds.
<b>System.Threading.ThreadStateException</b>	The caller attempted to join a thread that is in the <b>System.Threading.ThreadState.Unstarted</b> state.

# 1 Thread.MemoryBarrier () Method

```
2 [ILASM]  
3 .method public hidebysig static void MemoryBarrier ()  
4  
5 [C#]  
6 public static void MemoryBarrier ()
```

## 6 Summary

7 Guarantees that all subsequent loads or stores from the current thread  
8 will not access memory until after all previous loads and stores from  
9 the current thread have completed, as observed from this or other  
10 threads.

11



# Thread.ResetAbort() Method

```
[ILASM]
.method public hidebysig static void ResetAbort()

[C#]
public static void ResetAbort()
```

## Summary

Cancels a **System.Threading.Thread.Abort** requested for the current thread.

## Description

This method cannot be called by untrusted code.

When a call is made to **System.Threading.Thread.Abort** to destroy a thread, the system throws a **System.Threading.ThreadAbortException**. **System.Threading.ThreadAbortException** is a special exception that can be caught by application code, but is rethrown at the end of the catch block unless **ResetAbort** is called. **ResetAbort** cancels the request to abort, and prevents the **ThreadAbortException** from terminating the thread.

## Exceptions

Exception	Condition
<b>System.Threading.ThreadStateException</b>	<b>System.Threading.Thread.Abort</b> was not in current thread.
<b>System.Security.SecurityException</b>	Caller does not have <b>System.Security.Permissions.SecurityPermission</b> <b>ControlThread</b> security permission for the current thread.

## Example

For an example that demonstrates calling this method, see **System.Threading.ThreadAbortException**.

## Permissions

Permission	Description
<b>System.Security.SecurityPermission</b>	Requires permission to control the current thread. <b>System.Security.Permissions.SecurityPermission</b> <b>ControlThread</b>

1  
2  
3

	<b>ControlThread.</b>
--	-----------------------

# Thread.Sleep(System.Int32) Method

```
[ILASM]
.method public hidebysig static void Sleep(int32
millisecondsTimeout)

[C#]
public static void Sleep(int millisecondsTimeout)
```

## Summary

Blocks the current thread for the specified number of milliseconds.

## Parameters

Parameter	Description
<i>millisecondsTimeout</i>	A <b>System.Int32</b> containing the number of milliseconds for which the thread is blocked. Specify zero to indicate that this thread should be suspended temporarily to allow other waiting threads to execute. Specify <b>System.Threading.Timeout.Infinite</b> to block the thread indefinitely.

## Description

The thread will not be scheduled for execution by the operating system for the amount of time specified. This method changes the state of the thread to include **System.Threading.ThreadState.WaitSleepJoin**.

## Exceptions

Exception	Condition
<b>System.ArgumentOutOfRangeException</b>	The value of <i>millisecondsTimeout</i> is negative and is not equal to <b>System.Threading.Timeout.Infinite</b> .

# Thread.Sleep(System.TimeSpan) Method

```
[ILASM]
.method public hidebysig static void Sleep(valuetype
System.TimeSpan timeout)

[C#]
public static void Sleep(TimeSpan timeout)
```

## Summary

Blocks the current thread for a specified time.

## Parameters

Parameter	Description
<i>timeout</i>	A <b>System.TimeSpan</b> set to the amount of time for which the current thread will be blocked. Specify zero to indicate that this thread should be suspended temporarily to allow other waiting threads to execute. Specify <b>System.Threading.Timeout.Infinite</b> milliseconds to suspend the thread indefinitely.

## Description

This method converts *timeout* to milliseconds, tests the validity of the converted value, and calls **System.Threading.Thread.Sleep(System.Int32)**.

The thread will not be scheduled for execution by the operating system for the amount of time specified. This method changes the state of the thread to include **System.Threading.ThreadState.WaitSleepJoin**.

## Exceptions

Exception	Condition
<b>System.ArgumentOutOfRangeException</b>	The value of <i>timeout</i> is negative and is not equal to <b>System.Threading.Timeout.Infinite</b> milliseconds, or is greater than <b>System.Int32.MaxValue</b> milliseconds.

# Thread.Start() Method

```
[ILASM]
.method public hidebysig instance void Start()

[C#]
public void Start()
```

## Summary

Causes the operating system to consider the thread ready to be scheduled for execution.

## Description

Calling **System.Threading.Thread.Start** removes the **System.Threading.ThreadState.Unstarted** state from the **System.Threading.Thread.ThreadState** of the thread.

Once a thread is started, the operating system can schedule it for execution. When the thread begins executing, the **System.Threading.ThreadStart** delegate supplied to the constructor for the thread invokes its methods.

Once the thread terminates, it cannot be restarted with another call to **System.Threading.Thread.Start**.

## Exceptions

Exception	Condition
<b>System.OutOfMemoryException</b>	There is not enough memory available to start the thread.
<b>System.NullReferenceException</b>	This method was invoked on a <b>null</b> thread reference.
<b>System.Threading.ThreadStateException</b>	The thread has already been started.

## Example

The following example demonstrates creating a thread and starting it.

```
[C#]

using System;
using System.Threading;
public class ThreadWork {
    public static void DoWork() {
        for (int i = 0; i<3;i++) {
```

```

1         Console.WriteLine ("Working thread...");
2         Thread.Sleep(100);
3     }
4 }
5 }
6 class ThreadTest{
7     public static void Main() {
8         ThreadStart myThreadDelegate = new
9 ThreadStart(ThreadWork.DoWork);
10        Thread myThread = new Thread(myThreadDelegate);
11        myThread.Start();
12        for (int i = 0; i<3; i++) {
13            Console.WriteLine("In main.");
14            Thread.Sleep(100);
15        }
16    }
17 }
18

```

19 One possible set of output is

20  
21 In main.

22  
23  
24 Working thread...

25  
26  
27 In main.

28  
29  
30 Working thread...

31  
32  
33 In main.

34  
35

1       Working thread...

2

3

4       Note that the sequence of the output statements is not guaranteed to  
5       be identical across systems.

6

# Thread.VolatileRead(System.Byte&)

## Method

```
[ILASM]
.method public hidebysig static byte VolatileRead (class
System.Byte& address)

[C#]
public static byte VolatileRead (ref byte address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.Byte</b> that specifies the address in memory from which to read.

### Return Value

A **System.Byte** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]



# Thread.VolatileRead(System.Int16&)

## Method

```
[ILASM]
.method public hidebysig static int16 VolatileRead (class
System.Int16& address)

[C#]
public static short VolatileRead (ref short address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.Int16</b> that specifies the address in memory from which to read.

### Return Value

A **System.Int16** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileRead(System.Int32&)

## Method

```
[ILASM]
.method public hidebysig static int32 VolatileRead (class
System.Int32& address)

[C#]
public static int VolatileRead (ref int address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.Int32</b> that specifies the address in memory from which to read.

### Return Value

A **System.Int32** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# 1 Thread.VolatileRead(System.Int64&)

## 2 Method

```
3 [ILASM]
4 .method public hidebysig static int64 VolatileRead (class
5 System.Int64& address)
6
7 [C#]
8 public static long VolatileRead (ref long address)
```

### 8 Summary

9 Performs a volatile read from the specified address.

### 10 Parameters

11  
12

Parameter	Description
<i>address</i>	A <b>System.Int64</b> that specifies the address in memory from which to read.

13  
14  
15

### 14 Return Value

16 A **System.Int64** containing the value at the specified address after  
17 any pending writes.

### 18 Description

19 The value at the given address is atomically loaded with acquire  
20 semantics, meaning that the read is guaranteed to occur prior to any  
21 references to memory that occur after the execution of this method in  
22 the current thread. It is recommended that  
23 **System.Threading.Thread.VolatileRead** and  
24 **System.Threading.Thread.VolatileWrite** be used in conjunction.  
25 Calling this method affects only this single access; other accesses to  
26 the same location are required to also be made using this method or  
27 **System.Threading.Thread.VolatileWrite** if the volatile semantics  
28 are to be preserved. This method has exactly the same semantics as  
29 using the volatile prefix on the load IL instruction, except that  
30 atomicity is provided for all types, not just those 32 bits or smaller in  
31 size. [Note: For additional information, see Partition I of the CLI  
32 Specification.]

33

# Thread.VolatileRead(System.SByte&)

## Method

```
[ILASM]
.method public hidebysig static sbyte VolatileRead (class
System.Sbyte& address)

[C#]
public static sbyte VolatileRead (ref sbyte address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.SByte</b> that specifies the address in memory from which to read.

### Return Value

A **System.SByte** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileRead(System.UInt16&)

## Method

```
[ILASM]
.method public hidebysig static uint16 VolatileRead (class
System.UInt16& address)

[C#]
public static ushort VolatileRead (ref ushort address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.UInt16</b> that specifies the address in memory from which to read.

### Return Value

A **System.UInt16** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileRead(System.UInt32&)

## Method

```
[ILASM]
.method public hidebysig static uint32 VolatileRead (class
System.UInt32& address)

[C#]
public static uint VolatileRead (ref uint address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.UInt32</b> that specifies the address in memory from which to read.

### Return Value

A **System.UInt32** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

The following member must be implemented if the RuntimeInfrastructure library is present in the implementation.

## Thread.VolatileRead(System.IntPtr&) Method

```
[ILASM]  
.method public hidebysig static intptr VolatileRead (class  
System.IntPtr& address)
```

```
[C#]  
public static IntPtr VolatileRead (ref IntPtr address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.IntPtr</b> that specifies the address in memory from which to read.

### Return Value

A **System.IntPtr** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

The following member must be implemented if the RuntimeInfrastructure library is present in the implementation.

## Thread.VolatileRead(System.UIntPtr&) Method

```
[ILASM]
.method public hidebysig static uintPtr VolatileRead (class
System.UIntPtr& address)

[C#]
public static UIntPtr VolatileRead (ref UIntPtr address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.UIntPtr</b> that specifies the address in memory from which to read.

### Return Value

A **System.UIntPtr** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]



# Thread.VolatileRead(System.UInt64&)

## Method

```
[ILASM]
.method public hidebysig static uint64 VolatileRead (class
System.UInt64& address)

[C#]
public static ulong VolatileRead (ref ulong address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.UInt64</b> that specifies the address in memory from which to read.

### Return Value

A **System.UInt64** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# 1 Thread.VolatileRead(System.Single&)

## 2 Method

```
3 [ILASM]
4 .method public hidebysig static float32 VolatileRead (class
5 System.Single& address)
6
7 [C#]
8 public static float VolatileRead (ref float address)
```

### 8 Summary

9 Performs a volatile read from the specified address.

### 10 Parameters

11  
12

Parameter	Description
<i>address</i>	A <b>System.Single</b> that specifies the address in memory from which to read.

13  
14  
15

### 14 Return Value

16 A **System.Single** containing the value at the specified address after  
17 any pending writes.

### 18 Description

19 The value at the given address is atomically loaded with acquire  
20 semantics, meaning that the read is guaranteed to occur prior to any  
21 references to memory that occur after the execution of this method in  
22 the current thread. It is recommended that  
23 **System.Threading.Thread.VolatileRead** and  
24 **System.Threading.Thread.VolatileWrite** be used in conjunction.  
25 Calling this method affects only this single access; other accesses to  
26 the same location are required to also be made using this method or  
27 **System.Threading.Thread.VolatileWrite** if the volatile semantics  
28 are to be preserved. This method has exactly the same semantics as  
29 using the volatile prefix on the load IL instruction, except that  
30 atomicity is provided for all types, not just those 32 bits or smaller in  
31 size. [Note: For additional information, see Partition I of the CLI  
32 Specification.]

33

# Thread.VolatileRead(System.Double&)

## Method

```
[ILASM]
.method public hidebysig static float64 VolatileRead (class
System.Double& address)

[C#]
public static double VolatileRead (ref double address)
```

### Summary

Performs a volatile read from the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.Double</b> that specifies the address in memory from which to read.

### Return Value

A **System.Double** containing the value at the specified address after any pending writes.

### Description

The value at the given address is atomically loaded with acquire semantics, meaning that the read is guaranteed to occur prior to any references to memory that occur after the execution of this method in the current thread. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileWrite** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the load IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# 1 Thread.VolatileRead(System.Object&)

## 2 Method

```
3 [ILASM]
4 .method public hidebysig static object VolatileRead (class
5 System.Object& address)
6
7 [C#]
8 public static object VolatileRead (ref object address)
```

### 8 Summary

9 Performs a volatile read from the specified address.

### 10 Parameters

11  
12

Parameter	Description
<i>address</i>	A <b>System.Object</b> that specifies the address in memory from which to read.

13  
14  
15

### 14 Return Value

16 A **System.Object** containing the value at the specified address after  
17 any pending writes.

### 18 Description

19 The value at the given address is atomically loaded with acquire  
20 semantics, meaning that the read is guaranteed to occur prior to any  
21 references to memory that occur after the execution of this method in  
22 the current thread. It is recommended that  
23 **System.Threading.Thread.VolatileRead** and  
24 **System.Threading.Thread.VolatileWrite** be used in conjunction.  
25 Calling this method affects only this single access; other accesses to  
26 the same location are required to also be made using this method or  
27 **System.Threading.Thread.VolatileWrite** if the volatile semantics  
28 are to be preserved. This method has exactly the same semantics as  
29 using the volatile prefix on the load IL instruction, except that  
30 atomicity is provided for all types, not just those 32 bits or smaller in  
31 size. [Note: For additional information, see Partition I of the CLI  
32 Specification.]

33

# Thread.VolatileWrite(System.Byte&, System.Byte) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.Byte& address, byte value)

[C#]
public static void VolatileWrite (ref byte address, byte
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.Byte</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.Byte</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileWrite(System.Int16&, System.Int16) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.Int16& address, int16 value)

[C#]
public static void VolatileWrite (ref short address, short
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.Int16</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.Int16</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileWrite(System.Int32&, System.Int32) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.Int32& address, int32 value)

[C#]
public static void VolatileWrite (ref int address, int
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.Int32</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.Int32</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileWrite(System.Int64&, System.Int64) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.Int64& address, int64 value)

[C#]
public static void VolatileWrite (ref long address, long
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.Int64</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.Int64</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]



# Thread.VolatileWrite(System.SByte&, System.SByte) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.SByte& address, sbyte value)

[C#]
public static void VolatileWrite (ref sbyte address, sbyte
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.SByte</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.SByte</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileWrite(System.UInt16&, System.UInt16) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.UInt16& address, uint16 value)

[C#]
public static void VolatileWrite (ref ushort address,
ushort value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.UInt16</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.UInt16</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileWrite(System.UInt32&, System.UInt32) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.UInt32& address, uint32 value)

[C#]
public static void VolatileWrite (ref uint address, uint
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.UInt32</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.UInt32</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileWrite(UInt64&, System.UInt64) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.UInt64& address, uint64 value)

[C#]
public static void VolatileWrite (ref ulong address, ulong
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.UInt64</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.UInt64</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

The following member must be implemented if the RuntimeInfrastructure library is present in the implementation.

## Thread.VolatileWrite(System.UIntPtr&, System.UIntPtr) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.UIntPtr& address, UIntPtr value)

[C#]
public static void VolatileWrite (ref UIntPtr address,
UIntPtr value)
```

### Summary

Performs a volatile write to the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.UIntPtr</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.UIntPtr</b> that specifies the value to write.

### Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

The following member must be implemented if the RuntimeInfrastructure library is present in the implementation.

## Thread.VolatileWrite(System.IntPtr&, System.IntPtr) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.IntPtr& address, IntPtr value)

[C#]
public static void VolatileWrite (ref IntPtr address,
IntPtr value)
```

### Summary

Performs a volatile write to the specified address.

### Parameters

Parameter	Description
<i>address</i>	A <b>System.IntPtr</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.IntPtr</b> that specifies the value to write.

### Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# Thread.VolatileWrite(System.Single&, System.Single) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.Single& address, float32 value)

[C#]
public static void VolatileWrite (ref float address, float
value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.Single</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.Single</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# 1 Thread.VolatileWrite(System.Double&, 2 System.Double) Method

```
3 [ILASM]
4 .method public hidebysig static void VolatileWrite (class
5 System.Double& address, float64 value)

6 [C#]
7 public static void VolatileWrite (ref double address,
8 double value)
```

## 9 Summary

10 Performs a volatile write to the specified address.

## 11 Parameters

12  
13

Parameter	Description
<i>address</i>	A <b>System.Double</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.Double</b> that specifies the value to write.

14

## 15 Description

16 The value is written atomically to the specified address with release  
17 semantics, meaning that the write is guaranteed to happen after any  
18 references to memory that occur prior to the execution. It is  
19 recommended that **System.Threading.Thread.VolatileRead** and  
20 **System.Threading.Thread.VolatileWrite** be used in conjunction.  
21 Calling this method affects only this single access; other accesses to  
22 the same location are required to also be made using this method or  
23 **System.Threading.Thread.VolatileRead** if the volatile semantics  
24 are to be preserved. This method has exactly the same semantics as  
25 using the volatile prefix on the store IL instruction, except that  
26 atomicity is provided for all types, not just those 32 bits or smaller in  
27 size. [Note: For additional information, see Partition I of the CLI  
28 Specification.]

29



# Thread.VolatileWrite(System.Object&, System.Object) Method

```
[ILASM]
.method public hidebysig static void VolatileWrite (class
System.Object& address, object value)

[C#]
public static void VolatileWrite (ref object address,
object value)
```

## Summary

Performs a volatile write to the specified address.

## Parameters

Parameter	Description
<i>address</i>	A <b>System.Object</b> that specifies the address in memory at which to write.
<i>value</i>	A <b>System.Object</b> that specifies the value to write.

## Description

The value is written atomically to the specified address with release semantics, meaning that the write is guaranteed to happen after any references to memory that occur prior to the execution. It is recommended that **System.Threading.Thread.VolatileRead** and **System.Threading.Thread.VolatileWrite** be used in conjunction. Calling this method affects only this single access; other accesses to the same location are required to also be made using this method or **System.Threading.Thread.VolatileRead** if the volatile semantics are to be preserved. This method has exactly the same semantics as using the volatile prefix on the store IL instruction, except that atomicity is provided for all types, not just those 32 bits or smaller in size. [Note: For additional information, see Partition I of the CLI Specification.]

# 1 Thread.CurrentThread Property

```
2 [ILASM]
3 .property class System.Threading.Thread CurrentThread {
4 public hidebysig static specialname class
5 System.Threading.Thread get_CurrentThread() }

6 [C#]
7 public static Thread CurrentThread { get; }
```

## 8 Summary

9 Gets a **System.Threading.Thread** instance that represents the  
10 currently executing thread.

## 11 Property Value

12

13 An instance of **System.Threading.Thread** representing the current  
14 thread.

## 15 Description

16 This property is read-only.

17

# 1 Thread.IsAlive Property

```
2 [ILASM]
3 .property bool IsAlive { public hidebysig specialname
4 instance bool get_IsAlive() }

5 [C#]
6 public bool IsAlive { get; }
```

## 7 Summary

8 Gets a **System.Boolean** value indicating the execution status of the  
9 current thread.

## 10 Property Value

11

12 **true** if this thread has been started, and has not terminated;  
13 otherwise, **false**.

## 14 Description

15 This property is read-only.

16

17 This property returns true unless the  
18 **System.Threading.Thread.ThreadState** of the thread contains  
19 **System.Threading.ThreadState.Unstarted**, or  
20 **System.Threading.ThreadState.Stopped**.

21

# Thread.IsBackground Property

```
[ILASM]
.property bool IsBackground { public hidebysig specialname
instance bool get_IsBackground() public hidebysig
specialname instance void set_IsBackground(bool value) }

[C#]
public bool IsBackground { get; set; }
```

## Summary

Gets or sets a **System.Boolean** value indicating whether a thread is a background thread.

## Property Value

**true** if the thread is or is to become a background thread; otherwise, **false**.

## Description

The default value of this property is **false**. The property value can be changed before the thread is started and before it terminates.

[Note: A thread is either a background thread or a foreground thread. Background threads are identical to foreground threads except for the fact that background threads do not prevent a process from terminating. Once all foreground threads belonging to a process have terminated, the execution engine ends the process by invoking **System.Threading.Thread.Abort** on any background threads that are still alive.]

## Exceptions

Exception	Condition
<b>System.Threading.ThreadStateException</b>	The thread has reached the <b>System.Threading.ThreadState.Stopped</b> state.

# 1 Thread.Name Property

```
2 [ILASM]
3 .property string Name { public hidebysig specialname
4 instance string get_Name() public hidebysig specialname
5 instance void set_Name(string value) }

6 [C#]
7 public string Name { get; set; }
```

## 8 Summary

9 Gets or sets the name of the thread.

## 10 Property Value

11

12 A **System.String** containing the name of the thread, or **null** if no  
13 name was set.

## 14 Description

15 This property is write-once. Once this property has been set to a non-  
16 null value, attempts to set this property to a new value cause an  
17 exception.

## 18 Exceptions

19  
20

Exception	Condition
<b>System.InvalidOperationException</b>	A set operation was requested, and the <b>Name</b> property has already been set.

21  
22  
23

# Thread.Priority Property

```
[ILASM]
.property valuetype System.Threading.ThreadPriority
Priority { public hidebysig specialname instance valuetype
System.Threading.ThreadPriority get_Priority() public
hidebysig specialname instance void set_Priority(valuetype
System.Threading.ThreadPriority value) }
```

```
[C#]
public ThreadPriority Priority { get; set; }
```

## Summary

Gets or sets a value indicating the scheduling priority of a thread.

## Property Value

A **System.Threading.ThreadPriority** value.

## Description

A thread can be assigned any one of the following priority values:

- **System.Threading.ThreadPriority.Highest**
- **System.Threading.ThreadPriority.AboveNormal**
- **System.Threading.ThreadPriority.Normal**
- **System.Threading.ThreadPriority.BelowNormal**
- **System.Threading.ThreadPriority.Lowest**

The default value is **System.Threading.ThreadPriority.Normal**.

Operating systems are not required to honor the priority of a thread.

## Exceptions

Exception	Condition
<b>System.Threading.ThreadStateException</b>	The thread is in the <b>System.Threading.ThreadState.Stopped</b> state.
<b>System.ArgumentException</b>	The value specified for a set operation is not a valid

1  
2  
3

	<b>System.Threading.ThreadPriority</b> value.
--	---

# 1 Thread.ThreadState Property

```
2 [ILASM]
3 .property valuetype System.Threading.ThreadState
4 ThreadState { public hidebysig specialname instance
5 valuetype System.Threading.ThreadState get_ThreadState() }

6 [C#]
7 public ThreadState ThreadState { get; }
```

## 8 Summary

9 Gets a value containing the states of the current thread.

## 10 Property Value

11

12 A combination of one or more **System.Threading.ThreadState**  
13 values, which indicate the state of the current thread.

## 14 Description

15 This property is read-only.

16

17 A thread is running if the value returned by this property does not  
18 include **System.Threading.ThreadState.Unstarted** and does not  
19 include **System.Threading.ThreadState.Stopped**.

20