

System.InvalidProgramException Class

```
[ILASM]
.class public sealed serializable InvalidProgramException
extends System.SystemException

[C#]
public sealed class InvalidProgramException:
SystemException
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 1.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Summary

Represents the error that occurs when a program contains invalid IL instructions or metadata.

Inherits From: System.SystemException

Library: BCL

Thread Safety: All public static members of this type are safe for multithreaded operations. No instance members are guaranteed to be thread safe.

Description

[*Note:* This exception is thrown by the system when a compiler emits incorrect IL or metadata.]

InvalidProgramException() Constructor

```
[ILASM]  
public rtspecialname specialname instance void .ctor()  
  
[C#]  
public InvalidProgramException()
```

Summary

Constructs and initializes a new instance of the **System.InvalidProgramException** class.

Description

This constructor initializes the **System.InvalidProgramException.Message** property of the new instance to a system-supplied message that describes the error, such as "Metadata is incorrect." This message takes into account the current system culture.

The **System.InvalidProgramException.InnerException** property is initialized to **null**.

1 InvalidProgramException(System.String)

2 Constructor

```
3 [ILASM]  
4 public rtspecialname specialname instance void .ctor(string  
5 message)  
  
6 [C#]  
7 public InvalidProgramException(string message)
```

8 Summary

9 Constructs and initializes a new instance of the
10 **System.InvalidProgramException** class.

11 Parameters

12
13

Parameter	Description
<i>message</i>	A System.String that describes the error. The content of <i>message</i> is intended to be understood by humans. The caller of this constructor is required to ensure that this string has been localized for the current system culture.

14

15 Description

16 This constructor initializes the
17 **System.InvalidProgramException.Message** property of the new
18 instance using *message*. If *message* is **null**, the
19 **System.InvalidProgramException.Message** property is initialized
20 to the system-supplied message provided by the constructor that
21 takes no arguments. The
22 **System.InvalidProgramException.InnerException** property is
23 initialized to **null**.

24

InvalidProgramException(System.String, System.Exception) Constructor

```
[ILASM]
public rtspecialname specialname instance void .ctor(string
message, class System.Exception inner)

[C#]
public InvalidProgramException(string message, Exception
inner)
```

Summary

Constructs and initializes a new instance of the **System.InvalidProgramException** class.

Parameters

Parameter	Description
<i>message</i>	A System.String that describes the error. The content of <i>message</i> is intended to be understood by humans. The caller of this constructor is required to ensure that this string has been localized for the current system culture.
<i>inner</i>	An instance of System.Exception that is the cause of the current Exception. If <i>inner</i> is non-null, then the current Exception was raised in a catch block handling <i>inner</i> .

Description

This constructor initializes the **System.InvalidProgramException.Message** property of the new instance using *message*, and the **System.InvalidProgramException.InnerException** property using *inner*. If *message* is **null**, the **System.InvalidProgramException.Message** property is initialized to the system-supplied message provided by the constructor that takes no arguments.

[Note: For information on inner exceptions, see **System.Exception.InnerException**.]