

System.IO.StreamWriter Class

```
[ILAsm]
.class public serializable StreamWriter extends System.IO.TextWriter

[C#]
public class StreamWriter: TextWriter
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- **System.IDisposable**

Summary

Implements a `System.IO.Stream` wrapper that writes characters to a stream in a particular encoding.

Inherits From: System.IO.TextWriter

Library: BCL

Thread Safety: All public static members of this type are safe for multithreaded operations. No instance members are guaranteed to be thread safe.

Description

The `System.IO.StreamWriter` class is designed for character output in a particular `System.Text.Encoding`, whereas subclasses of `System.IO.Stream` are designed for byte input and output.

`System.IO.StreamWriter` defaults to using an instance of `System.Text.UTF8Encoding` unless specified otherwise. This instance of `System.Text.UTF8Encoding` is constructed such that the `System.Text.Encoding.GetPreamble` method returns the Unicode byte order mark written in UTF-8. The preamble of the encoding is added to a stream when you are not appending to an existing stream. This means any text file you create with `System.IO.StreamWriter` has three byte order marks at its beginning. UTF-8 handles all Unicode characters correctly and gives consistent results on localized versions of the operating system.

[*Note:* By default, `System.IO.StreamWriter` is not thread safe. For a thread-safe

wrapper, see `System.IO.TextWriter.Synchronized`.]

StreamWriter(System.String, System.Boolean, System.Text.Encoding, System.Int32) Constructor

```
[ILAsm]
public rtspecialname specialname instance void .ctor(string path,
bool append, class System.Text.Encoding encoding, int32 bufferSize)

[C#]
public StreamWriter(string path, bool append, Encoding encoding, int
bufferSize)
```

Summary

Constructs and initializes a new instance of the `System.IO.StreamWriter` class for the specified file on the specified path, using the specified encoding and buffer size.

Parameters

Parameter	Description
<i>path</i>	A <code>System.String</code> that specifies the complete file path to write to.
<i>append</i>	A <code>System.Boolean</code> value that determines whether data is to be appended to the file. If the file exists and <i>append</i> is <code>false</code> , the file is overwritten. If the file exists and <i>append</i> is <code>true</code> , the data is appended to the file. Otherwise, a new file is created.
<i>encoding</i>	A <code>System.Text.Encoding</code> that specifies the character encoding to use.
<i>bufferSize</i>	A <code>System.Int32</code> that specifies the buffer size.

Description

If the specified file exists, it can be either overwritten or appended to. If the file does not exist, this constructor creates a new file.

This constructor initializes the `System.IO.StreamWriter.Encoding` property using *encoding*. For additional information, see `System.IO.TextWriter.Encoding`.

[*Note:* *path* is not required to be a file stored on disk; it can be any part of a system that supports access via streams. For example, depending on the system, this class might be able to access a physical device.

For information on the valid format and characters for path strings, see `System.IO.Path`.

]

Exceptions

Exception	Condition
System.IO.IOException	A general I/O exception occurred, such as trying to access a CD-ROM drive whose tray is open.
System.IO.DirectoryNotFoundException	The directory information specified in <i>path</i> was not found.
System.ArgumentException	<i>path</i> is a zero-length string, contains only white space, or contains one or more implementation-specific invalid characters.
System.ArgumentNullException	<i>path</i> or <i>encoding</i> is null.
System.IO.NotSupportedException	<i>path</i> is in an implementation-specific invalid format.
System.IO.PathTooLongException	The length of <i>path</i> or the absolute path information for <i>path</i> exceeds the implementation-specific maximum length.
System.ArgumentOutOfRangeException	<i>bufferSize</i> is negative.
System.Security.SecurityException	The caller does not have the required permission.
System.UnauthorizedAccessException	Access is denied. The caller does not have the required permission.

Permissions

Permission	Description
System.Security.Permissions.FileIOPermission	Requires permission for reading and writing files. See <code>System.Security.Permissions.FileIOPermissionAccess.Read</code> , <code>System.Security.Permissions.FileIOPermissionAccess.Write</code>

StreamWriter(System.String, System.Boolean, System.Text.Encoding) Constructor

```
[ILAsm]  
public rtspecialname specialname instance void .ctor(string path,  
bool append, class System.Text.Encoding encoding)
```

```
[C#]  
public StreamWriter(string path, bool append, Encoding encoding)
```

Summary

Constructs and initializes a new instance of the `System.IO.StreamWriter` class for the specified file on the specified path, using the specified encoding and default buffer size.

Parameters

Parameter	Description
<i>path</i>	A <code>System.String</code> that specifies the complete file path to write to.
<i>append</i>	A <code>System.Boolean</code> value that determines whether data is to be appended to the file. If the file exists and <i>append</i> is <code>false</code> , the file is overwritten. If the file exists and <i>append</i> is <code>true</code> , the data is appended to the file. Otherwise, a new file is created.
<i>encoding</i>	A <code>System.Text.Encoding</code> that specifies the character encoding to use.

Description

If the specified file exists, it can be either overwritten or appended to. If the file does not exist, this constructor creates a new file.

This constructor initializes the `System.IO.StreamWriter.Encoding` property using *encoding*. For additional information, see `System.IO.TextWriter.Encoding`.

[*Note:* *path* is not required to be a file stored on disk; it can be any part of a system that supports access via streams. For example, depending on the system, this class might be able to access a physical device.

For information on the valid format and characters for path strings, see `System.IO.Path`.

The default buffer size can typically be around 4 KB.

]

Exceptions

Exception	Condition
System.IO.IOException	A general I/O exception occurred, such as trying to access a CD-ROM drive whose tray is open.
System.IO.DirectoryNotFoundException	The directory information specified in <i>path</i> was not found.
System.UnauthorizedAccessException	Access is denied. The caller does not have the required permission.
System.ArgumentException	<i>path</i> is a zero-length string, contains only white space, or contains one or more implementation-specific invalid characters.
System.ArgumentNullException	<i>path</i> or <i>encoding</i> is null.
System.IO.NotSupportedException	<i>path</i> is in an implementation-specific invalid format.
System.IO.PathTooLongException	The length of <i>path</i> or the absolute path information for <i>path</i> exceeds the implementation-specific maximum length.
System.Security.SecurityException	The caller does not have the required permission.

Permissions

Permission	Description
System.Security.Permissions.FileIOPermission	Requires permission for reading and writing files. See <code>System.Security.Permissions.FileIOPermissionAccess.Read</code> , <code>System.Security.Permissions.FileIOPermissionAccess.Write</code>

StreamWriter(System.String, System.Boolean) Constructor

```
[ILAsm]  
public rtspecialname specialname instance void .ctor(string path,  
bool append)  
  
[C#]  
public StreamWriter(string path, bool append)
```

Summary

Constructs and initializes a new instance of the `System.IO.StreamWriter` class for the specified file on the specified path, using the default encoding and buffer size.

Parameters

Parameter	Description
<i>path</i>	A <code>System.String</code> that specifies the complete file path to write to.
<i>append</i>	A <code>System.Boolean</code> value that determines whether data is to be appended to the file. If the file exists and <i>append</i> is <code>false</code> , the file is overwritten. If the file exists and <i>append</i> is <code>true</code> , the data is appended to the file. Otherwise, a new file is created.

Description

This constructor initializes the `System.IO.StreamWriter.Encoding` property to `System.Text.UTF8Encoding` whose `System.Text.Encoding.GetPreamble` method returns an empty byte array. For additional information, see `System.IO.TextWriter.Encoding`.

If the specified file exists, it can be either overwritten or appended to. If the file does not exist, this constructor creates a new file.

[*Note:* *path* is not required to be a file stored on disk; it can be any part of a system that supports access via streams. For example, depending on the system, this class might be able to access a physical device.

For information on the valid format and characters for path strings, see `System.IO.Path`.

The default buffer size can typically be around 4 KB.

]

Exceptions

Exception	Condition
System.IO.IOException	A general I/O exception occurs, such as trying to access a CD-ROM drive whose tray is open
System.IO.DirectoryNotFoundException	The directory information specified in <i>path</i> was not found.
System.UnauthorizedAccessException	Access to <i>path</i> is denied. The caller does not have the required permission.
System.ArgumentException	<i>path</i> is a zero-length string, contains only white space, or contains one or more implementation-specific invalid characters.
System.IO.NotSupportedException	<i>path</i> is in an implementation-specific invalid format.
System.IO.PathTooLongException	The length of <i>path</i> or the absolute path information for <i>path</i> exceeds the implementation-specific maximum length.
System.ArgumentNullException	<i>path</i> is null.
System.Security.SecurityException	The caller does not have the required permission.

Permissions

Permission	Description
System.Security.Permissions.FileIOPermission	Requires permission for reading and writing files. See <code>System.Security.Permissions.FileIOPermissionAccess.Read</code> , <code>System.Security.Permissions.FileIOPermissionAccess.Write</code>

StreamWriter(System.IO.Stream) Constructor

```
[ILAsm]  
public rtspecialname specialname instance void .ctor(class  
System.IO.Stream stream)  
  
[C#]  
public StreamWriter(Stream stream)
```

Summary

Constructs and initializes a new instance of the `System.IO.StreamWriter` class for the specified stream, using the default encoding and buffer size.

Parameters

Parameter	Description
<i>stream</i>	The <code>System.IO.Stream</code> to write to.

Description

This constructor initializes the `System.IO.StreamWriter.Encoding` property to a `System.Text.UTF8Encoding` whose `System.Text.Encoding.GetPreamble` method returns an empty byte array. For additional information, see `System.IO.TextWriter.Encoding`. The `System.IO.StreamWriter.BaseStream` property is initialized using *stream*.

[*Note:* The default buffer size can typically be around 4 KB.]

Exceptions

Exception	Condition
<code>System.ArgumentException</code>	<i>stream</i> does not support writing.
<code>System.ArgumentNullException</code>	<i>stream</i> is null.

StreamWriter(System.IO.Stream, System.Text.Encoding) Constructor

```
[ILAsm]
public rtspecialname specialname instance void .ctor(class
System.IO.Stream stream, class System.Text.Encoding encoding)

[C#]
public StreamWriter(Stream stream, Encoding encoding)
```

Summary

Constructs and initializes a new instance of the `System.IO.StreamWriter` class for the specified stream, using the specified encoding and the default buffer size.

Parameters

Parameter	Description
<i>stream</i>	The <code>System.IO.Stream</code> to write to.
<i>encoding</i>	A <code>System.Text.Encoding</code> that specifies the character encoding to use.

Description

This constructor initializes the `System.IO.StreamWriter.Encoding` property using *encoding*, and the `System.IO.StreamWriter.BaseStream` property using *stream*. For additional information, see `System.IO.TextWriter.Encoding`.

[*Note:* The default buffer size can typically be around 4 KB.]

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<i>stream</i> or <i>encoding</i> is null.
<code>System.ArgumentException</code>	<i>stream</i> does not support writing.

StreamWriter(System.IO.Stream, System.Text.Encoding, System.Int32) Constructor

```
[ILAsm]
public rtspecialname specialname instance void .ctor(class
System.IO.Stream stream, class System.Text.Encoding encoding, int32
bufferSize)
```

```
[C#]
public StreamWriter(Stream stream, Encoding encoding, int
bufferSize)
```

Summary

Constructs and initializes a new instance of the `System.IO.StreamWriter` class for the specified stream, using the specified encoding and buffer size.

Parameters

Parameter	Description
<i>stream</i>	The <code>System.IO.Stream</code> to write to.
<i>encoding</i>	A <code>System.Text.Encoding</code> that specifies the character encoding to use.
<i>bufferSize</i>	A <code>System.Int32</code> that specifies the buffer size.

Description

This constructor initializes the `System.IO.StreamWriter.Encoding` property using *encoding*, and the `System.IO.StreamWriter.BaseStream` property using *stream*. For additional information, see `System.IO.TextWriter.Encoding`.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<i>stream</i> or <i>encoding</i> is null.
<code>System.ArgumentOutOfRangeException</code>	<i>bufferSize</i> is negative.
<code>System.ArgumentException</code>	<i>stream</i> does not support writing.

StreamWriter(System.String) Constructor

```
[ILAsm]
public rtspecialname specialname instance void .ctor(string path)

[C#]
public StreamWriter(string path)
```

Summary

Constructs and initializes a new instance of the `System.IO.StreamWriter` class for the specified file on the specified path, using the default encoding and buffer size.

Parameters

Parameter	Description
<i>path</i>	A <code>System.String</code> that specifies the complete file path to write to.

Description

This constructor initializes the `System.IO.StreamWriter.Encoding` property to a `System.Text.UTF8Encoding` whose `System.Text.Encoding.GetPreamble` method returns an empty byte array. For additional information, see `System.IO.TextWriter.Encoding`.

[*Note:* *path* is not required to be a file stored on disk; it can be any part of a system that supports access via streams. For example, depending on the system, this class might be able to access a physical device.

For information on the valid format and characters for path strings, see `System.IO.Path`.

The default buffer size can typically be around 4 KB.

]

Exceptions

Exception	Condition
<code>System.IO.IOException</code>	<i>path</i> is in an invalid format or contains invalid characters.
<code>System.IO.DirectoryNotFoundException</code>	The directory information specified in <i>path</i> was not found.
<code>System.UnauthorizedAccessException</code>	Access to <i>path</i> is denied.

System.ArgumentException	<i>path</i> is an empty string ("").
System.ArgumentNullException	<i>path</i> is null.
System.IO.PathTooLongException	The length of <i>path</i> or the absolute path information for <i>path</i> exceeds the implementation-specific maximum length.
System.Security.SecurityException	The caller does not have the required permission.

Permissions

Permission	Description
System.Security.Permissions.FileIOPermission	Requires permission for reading and writing files. See <code>System.Security.Permissions.FileIOPermissionAccess.Read</code> , <code>System.Security.Permissions.FileIOPermissionAccess.Write</code>

StreamWriter.Close() Method

```
[ILAsm]  
.method public hidebysig virtual void Close()  
  
[C#]  
public override void Close()
```

Summary

Closes the current `System.IO.StreamWriter` and the underlying stream.

Description

This method calls `System.IO.StreamWriter.Flush`, writing buffered data to the underlying stream. Following a call to `System.IO.StreamWriter.Close`, any operations on the current instance might raise exceptions.

[*Note:* This version of `System.IO.StreamWriter.Close` is equivalent to `System.IO.StreamWriter.Dispose(true)`.

This method overrides `System.IO.Stream.Close`.

]

StreamWriter.Dispose(System.Boolean) Method

```
[ILAsm]  
.method family hidebysig virtual void Dispose(bool disposing)
```

```
[C#]  
protected override void Dispose(bool disposing)
```

Summary

Releases the unmanaged resources used by the `System.IO.StreamWriter` and optionally releases the managed resources.

Parameters

Parameter	Description
<i>disposing</i>	true to release both managed and unmanaged resources; false to release only unmanaged resources.

Description

When the *disposing* parameter is `true`, this method releases all resources held by any managed objects that this `System.IO.StreamWriter` references. This method invokes the `Dispose()` method of each referenced object.

[*Note:* `System.IO.StreamWriter.Dispose` can be called multiple times by other objects. When overriding `System.IO.StreamWriter.Dispose(System.Boolean)`, be careful not to reference objects that have been previously disposed in an earlier call to `System.IO.StreamWriter.Dispose`.

This method calls the `dispose` method of the base class, `System.IO.TextWriter.Dispose(disposing)`.

]

StreamWriter.Finalize() Method

```
[ILAsm]  
.method family hidebysig virtual void Finalize()  
  
[C#]  
~StreamWriter()
```

Summary

Releases resources held by the current instance.

Description

[*Note:* Application code does not call this method; it is automatically invoked by during garbage collection unless finalization by the garbage collector has been disabled. For more information, see `System.GC.SuppressFinalize`, and `System.Object.Finalize`.

This method overrides `System.Object.Finalize`.

]

StreamWriter.Flush() Method

```
[ILAsm]  
.method public hidebysig virtual void Flush()  
  
[C#]  
public override void Flush()
```

Summary

Clears all buffers for the current writer and causes any buffered data to be written to the underlying stream.

Description

[*Note:* This method overrides `System.IO.TextWriter.Flush`.]

Exceptions

Exception	Condition
<code>System.ObjectDisposedException</code>	The current writer is closed.
<code>System.IO.IOException</code>	An I/O error occurred.

StreamWriter.Write(System.Char) Method

```
[ILAsm]  
.method public hidebysig virtual void Write(valuetype System.Char  
value)
```

```
[C#]  
public override void Write(char value)
```

Summary

Writes a character to the stream.

Parameters

Parameter	Description
<i>value</i>	The <code>System.Char</code> to write to the underlying stream.

Description

The specified character is written to the underlying stream unless the end of the stream is reached prematurely.

If `System.IO.StreamWriter.AutoFlush` is true, `System.IO.StreamWriter.Flush` is invoked automatically.

[*Note:* This method overrides `System.IO.TextWriter.Write`.]

Exceptions

Exception	Condition
System.NotSupportedException	<code>System.IO.StreamWriter.AutoFlush</code> is true or the <code>System.IO.StreamWriter</code> buffer is full, and the contents of the buffer cannot be written to the underlying fixed size stream because the <code>System.IO.StreamWriter</code> is at the end the stream.
System.ObjectDisposedException	The current writer is closed.
System.IO.IOException	An I/O error occurred.

StreamWriter.Write(System.Char[]) Method

```
[ILAsm]  
.method public hidebysig virtual void Write(char[] buffer)  
  
[C#]  
public override void Write(char[] buffer)
```

Summary

Writes a character array to the underlying stream.

Parameters

Parameter	Description
<i>buffer</i>	A <code>System.Char</code> array containing the data to write. If <i>buffer</i> is null, nothing is written.

Description

The specified characters are written to the underlying stream unless the end of the stream is reached prematurely.

If `System.IO.StreamWriter.AutoFlush` is true, `System.IO.StreamWriter.Flush` is invoked automatically.

[*Note:* This method overrides `System.IO.TextWriter.Write`.]

Exceptions

Exception	Condition
System.NotSupportedException	<code>System.IO.StreamWriter.AutoFlush</code> is true or the <code>System.IO.StreamWriter</code> buffer is full, and the contents of the buffer cannot be written to the underlying fixed size stream because the <code>System.IO.StreamWriter</code> is at the end the stream.
System.ObjectDisposedException	The current writer is closed.
System.IO.IOException	An I/O error occurred.

StreamWriter.Write(System.Char[], System.Int32, System.Int32) Method

```
[ILAsm]
.method public hidebysig virtual void Write(char[] buffer, int32
index, int32 count)

[C#]
public override void Write(char[] buffer, int index, int count)
```

Summary

Writes a sub-array of characters to the underlying stream.

Parameters

Parameter	Description
<i>buffer</i>	A <code>System.Char</code> array containing the data to write.
<i>index</i>	A <code>System.Int32</code> that specifies the index into <i>buffer</i> at which to begin writing.
<i>count</i>	A <code>System.Int32</code> that specifies the number of characters to read from <i>buffer</i> .

Description

The specified characters are written to the underlying stream unless the end of the stream is reached prematurely.

If `System.IO.StreamWriter.AutoFlush` is true, `System.IO.StreamWriter.Flush` is invoked automatically.

[*Note:* This method overrides `System.IO.TextWriter.Write`.]

Exceptions

Exception	Condition
<code>System.ArgumentException</code>	<code>buffer.Length - index < count</code> .
<code>System.ArgumentNullException</code>	<i>buffer</i> is null.
<code>System.ArgumentOutOfRangeException</code>	<i>index</i> or <i>count</i> is negative.
<code>System.NotSupportedException</code>	<code>System.IO.StreamWriter.AutoFlush</code> is true or the <code>System.IO.StreamWriter</code> buffer is full, and the contents of the

	buffer cannot be written to the underlying fixed size stream because the <code>System.IO.StreamWriter</code> is at the end the stream.
System.ObjectDisposedException	The current writer is closed.
System.IO.IOException	An I/O error occurred.

StreamWriter.Write(System.String) Method

```
[ILAsm]  
.method public hidebysig virtual void Write(string value)  
  
[C#]  
public override void Write(string value)
```

Summary

Writes a string to the stream.

Parameters

Parameter	Description
<i>value</i>	The <code>System.String</code> to write to the stream. If <i>value</i> is null, nothing is written.

Description

The specified `System.String` is written to the underlying stream unless the end of the stream is reached prematurely.

If `System.IO.StreamWriter.AutoFlush` is true, `System.IO.StreamWriter.Flush` is invoked automatically.

[*Note:* This method overrides `System.IO.TextWriter.Write`.]

Exceptions

Exception	Condition
System.NotSupportedException	<code>System.IO.StreamWriter.AutoFlush</code> is true or the <code>System.IO.StreamWriter</code> buffer is full, and the contents of the buffer cannot be written to the underlying fixed size stream because the <code>System.IO.StreamWriter</code> is at the end the stream.
System.ObjectDisposedException	The current writer is closed.
System.IO.IOException	An I/O error occurred.

StreamWriter.AutoFlush Property

```
[ILAsm]
.property bool AutoFlush { public hidebysig virtual specialname bool
get_AutoFlush() public hidebysig virtual specialname void
set_AutoFlush(bool value) }

[C#]
public virtual bool AutoFlush { get; set; }
```

Summary

Gets or sets a `System.Boolean` value indicating whether the current `System.IO.StreamWriter` will flush its buffer to the underlying stream after every call to `System.IO.StreamWriter.Write`.

Property Value

true to force `System.IO.StreamWriter` to flush its buffer; otherwise, false.

Description

The `System.IO.StreamWriter` will do a limited amount of buffering, both internally and potentially in the encoder from the encoding you passed in. If `System.IO.StreamWriter.AutoFlush` is set to false, the data will be flushed into the underlying stream only when the buffer is full, or when `System.IO.StreamWriter.Dispose(true)` or `System.IO.StreamWriter.Close` is called.

Setting `System.IO.StreamWriter.AutoFlush` to true forces `System.IO.StreamWriter` to flush the buffered data out of the encoder and call `System.IO.StreamWriter.Flush` on the stream every time `System.IO.StreamWriter.Write` is called.

Behaviors

As described above.

StreamWriter.BaseStream Property

```
[ILAsm]  
.property class System.IO.Stream BaseStream { public hidebyref  
virtual specialname class System.IO.Stream get_BaseStream() }
```

```
[C#]  
public virtual Stream BaseStream { get; }
```

Summary

Gets the underlying stream.

Property Value

The `System.IO.Stream` the current `System.IO.StreamWriter` instance is writing to.

Behaviors

As described above.

StreamWriter.Encoding Property

```
[ILAsm]  
.property class System.Text.Encoding Encoding { public hidebysig  
virtual specialname class System.Text.Encoding get_Encoding() }  
  
[C#]  
public override Encoding Encoding { get; }
```

Summary

Gets the `System.Text.Encoding` in which the output is written.

Property Value

The `System.Text.Encoding` specified in the constructor for the current instance, or `System.Text.UTF8Encoding` if an encoding was not specified.

Description

[*Note:* This property overrides the `System.IO.TextWriter.Encoding` property.]

Behaviors

As described above.

Usage

This property is required in some XML scenarios where a header must be written containing the encoding used by the `System.IO.StreamWriter`. This allows XML code to consume an arbitrary `System.IO.StreamWriter` and generate a correct XML header.