

# System.RuntimeFieldHandle Structure

```
[ILAsm]
.class public sequential sealed serializable RuntimeFieldHandle extends
System.ValueType

[C#]
public struct RuntimeFieldHandle
```

## Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
  - CLSCompliantAttribute(true)

## Summary

Serves as a metadata token for a field.

## Inherits From: System.ValueType

**Library:** RuntimeInfrastructure

**Thread Safety:** All public static members of this type are safe for multithreaded operations. No instance members are guaranteed to be thread safe.

## Description

System.RuntimeFieldHandle objects are created through the use of the CIL instruction `ldtoken`.

[*Note:* For more information on `ldtoken`, see Partition III of the CLI Specification.]

# RuntimeFieldHandle.Value Property

```
[ILAsm]  
.property valuetype System.IntPtr Value { public hidebysig specialname  
instance valuetype System.IntPtr get_Value() }  
  
[C#]  
public IntPtr Value { get; }
```

## Summary

Gets a System.IntPtr that contains the value of the current System.RuntimeFieldHandle.

## Property Value

A System.IntPtr that contains the value of the current System.RuntimeFieldHandle.

## Description

This property is read-only.